

2016 RAM 1500 Trailer Towing Chart - SAE J2807 Compliant											
Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
STD CAB - 6'4" Box, 4x2, HFE											
3.6 V6	A8 845RE	3.21	6010	1440	4570.76	2518.27	2052.49	3,700	3,900	9,850	4,970
STD CAB - 6'4" Box, 4x2, R/T											
5.7L V8 HEMI	A8 8HP70	3.92	6200	1350	4847.76	2757.96	2089.80	3,700	3,900	10,250	5,030
STD CAB - 6'4" Box, 4x2											
3.6L V6	A8 845RE	3.21	6025	1500	4523.90	2500.92	2022.98	3,700	3,900	9,850	4,990
3.6L V6	A8 845RE	3.55	6025	1500	4523.90	2500.92	2022.98	3,700	3,900	12,200	7,290
5.7L V8 HEMI	A6 65RFE	3.21	6350	1600	4746.54	2725.50	2021.04	3,700	3,900	12,350	7,220
5.7L V8 HEMI	A6 65RFE	3.92	6350	1600	4746.54	2725.50	2021.04	3,700	3,900	14,325	9,200
5.7L V8 HEMI	A8 8HP70	3.21	6350	1590	4761.99	2736.07	2025.92	3,700	3,900	13,800	8,610
5.7L V8 HEMI	A8 8HP70	3.92	6350	1590	4761.99	2736.07	2025.92	3,700	3,900	14,350	9,160
STD CAB - 6'4" Box, 4x4											
3.6L V6	A8 845RE	3.21	6300	1560	4738.82	2678.77	2060.05	3,900	3,900	9,850	4,760
3.6L V6	A8 845RE	3.55	6300	1560	4738.82	2678.77	2060.05	3,900	3,900	12,200	7,050
5.7L V8 HEMI	A6 65RFE	3.55	6350	1400	4953.92	2896.25	2057.67	3,900	3,900	14,400	9,060
5.7L V8 HEMI	A6 65RFE	3.92	6350	1400	4953.92	2896.25	2057.67	3,900	3,900	14,325	8,990
5.7L V8 HEMI	A8 8HP70	3.21	6350	1390	4959.57	2895.57	2064.00	3,900	3,900	13,800	8,420
5.7L V8 HEMI	A8 8HP70	3.92	6350	1390	4959.57	2895.57	2064.00	3,900	3,900	14,350	8,970

- 1 Payload and Max Trailer Weights are ESTIMATED values.
- 2 All weights are shown in pounds unless otherwise stated.
- 3 Payload and Max Trailer Weight values are rounded to the nearest 10 lb.
- 4 Payload = GVWR – Base Weight.
- 5 Trailer Weight Rating and Tow Vehicle Trailering Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb.
 Options Weight is option content above 33 percent of sales volume.
 Trailer equipment weight =
 Class IV receiver hitch is 11.1 lb (if not already included in options weight).
 Trailer Hitch is 10 lb if TWR is less or equal to 5,000 lb and 65 lb if TWR is greater than 5,000 lb.
- 6 Payload and Trailer Weight Rating are mutually exclusive.
- 7 GAWRs, GVWRs and GCWRs should never be exceeded.
- 8 The recommended tongue weight for a conventional hitch is 10 percent of the gross trailer weight. The maximum tongue weight for Class IV receiver hitch is limited to 1100 lb.
- 9 Weight Distributing Hitch is recommended for trailers over 5,000 lb.
- 10 Quad Cab and Crew Cab models with Off Road Tire (s/c TXN), All Terrain Tire (s/c TWG) or Steel Wheel (s/c WFP) have 6800 lb GVWR.
- 11 All models with 22 inch Tires (s/c TY4) have 6200 lb GVWR.
- 12 Big Horn and Lone Star packages equipped with the 3.0L V6 EcoDiesel Engine and a 3.92 axle ratio have 13,750 lb. GCWR.

2016 RAM 1500 Trailer Towing Chart - SAE J2807 Compliant											
Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
STD CAB - 8' Box, 4x2											
3.6L V6	A8 845RE	3.21	6600	1880	4718.50	2662.99	2055.51	3,700	3,900	9,850	4,770
3.6L V6	A8 845RE	3.55	6600	1880	4718.50	2662.99	2055.51	3,700	3,900	12,400	7,270
5.7L V8 HEMI	A6 65RFE	3.21	6600	1700	4899.87	2865.43	2034.44	3,700	3,900	12,350	7,040
5.7L V8 HEMI	A6 65RFE	3.55	6600	1700	4899.87	2865.43	2034.44	3,700	3,900	14,400	9,090
5.7L V8 HEMI	A6 65RFE	3.92	6600	1700	4899.87	2865.43	2034.44	3,700	3,900	15,950	10,640
5.7L V8 HEMI	A8 8HP70	3.21	6600	1690	4914.89	2801.03	2113.86	3,700	3,900	13,800	8,470
5.7L V8 HEMI	A8 8HP70	3.92	6600	1690	4914.89	2801.03	2113.86	3,700	3,900	15,950	10,620
3.0L V6 ECODIESEL	A8 8HP70	3.55	6600	1510	5094.89	2902.61	2192.28	3,700	3,900	13,750	8,240
3.0L V6 ECODIESEL	A8 8HP70	3.92	6600	1510	5094.89	2902.61	2192.28	3,700	3,900	13,750	8,240
3.0L V6 ECODIESEL	A8 8HP70	3.92	6600	1510	5094.89	2902.61	2192.28	3,700	3,900	14,750	9,210
STD CAB - 8' Box, 4x4											
3.6L V6	A8 845RE	3.21	6600	1690	4910.37	2869.40	2040.97	3,900	3,900	9,850	4,580
3.6L V6	A8 845RE	3.55	6600	1690	4910.37	2869.40	2040.97	3,900	3,900	12,400	7,080
5.7L V8 HEMI	A6 65RFE	3.55	6600	1470	5128.56	3038.36	2090.20	3,900	3,900	14,400	8,850
5.7L V8 HEMI	A6 65RFE	3.92	6600	1470	5128.56	3038.36	2090.20	3,900	3,900	15,950	10,400
5.7L V8 HEMI	A8 8HP70	3.21	6600	1480	5117.22	3043.92	2073.30	3,900	3,900	13,800	8,260
5.7L V8 HEMI	A8 8HP70	3.92	6600	1480	5117.22	3043.92	2073.30	3,900	3,900	15,950	10,410
3.0L V6 ECODIESEL	A8 8HP70	3.55	6600	1290	5312.24	3203.55	2108.69	3,900	3,900	13,750	8,030
3.0L V6 ECODIESEL	A8 8HP70	3.92	6600	1290	5312.24	3203.55	2108.69	3,900	3,900	13,750	8,030
3.0L V6 ECODIESEL	A8 8HP70	3.92	6600	1290	5312.24	3203.55	2108.69	3,900	3,900	14,750	9,030

- 1 Payload and Max Trailer Weights are ESTIMATED values.
- 2 All weights are shown in pounds unless otherwise stated.
- 3 Payload and Max Trailer Weight values are rounded to the nearest 10 lb.
- 4 Payload = GVWR – Base Weight.
- 5 Trailer Weight Rating and Tow Vehicle Trailering Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb.
 Options Weight is option content above 33 percent of sales volume.
 Trailer equipment weight =
 Class IV receiver hitch is 11.1 lb (if not already included in options weight).
 Trailer Hitch is 10 lb if TWR is less or equal to 5,000 lb and 65 lb if TWR is greater than 5,000 lb.
- 6 Payload and Trailer Weight Rating are mutually exclusive.
- 7 GAWRs, GVWRs and GCWRs should never be exceeded.
- 8 The recommended tongue weight for a conventional hitch is 10 percent of the gross trailer weight. The maximum tongue weight for Class IV receiver hitch is limited to 1100 lb.
- 9 Weight Distributing Hitch is recommended for trailers over 5,000 lb.
- 10 Quad Cab and Crew Cab models with Off Road Tire (s/c TXN), All Terrain Tire (s/c TWG) or Steel Wheel (s/c WFP) have 6800 lb GVWR.
- 11 All models with 22 inch Tires (s/c TY4) have 6200 lb GVWR.
- 12 Big Horn and Lone Star packages equipped with the 3.0L V6 EcoDiesel Engine and a 3.92 axle ratio have 13,750 lb. GCWR.

2016 RAM 1500 Trailer Towing Chart - SAE J2807 Compliant											
Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
QUAD CAB - 6'4" Box 4x2 - HFE											
3.0L V6 ECODIESEL	A8 8HP70	3.55	6945	1510	5435.60	3105.30	2330.30	3,700	3,900	13,750	7,940
QUAD CAB - 6'4" Box 4x2											
3.6L V6	A8 845RE	3.21	6800	1890	4914.61	2742.95	2171.66	3,700	3,900	9,850	4,610
3.6L V6	A8 845RE	3.55	6800	1890	4914.61	2742.95	2171.66	3,700	3,900	12,900	7,610
5.7L V8 HEMI	A6 65RFE	3.21	6900	1800	5100.13	2957.51	2142.62	3,700	3,900	12,350	6,790
5.7L V8 HEMI	A6 65RFE	3.55	6900	1800	5100.13	2957.51	2142.62	3,700	3,900	14,400	8,840
5.7L V8 HEMI	A6 65RFE	3.92	6900	1800	5100.13	2957.51	2142.62	3,700	3,900	15,950	10,390
5.7L V8 HEMI	A8 8HP70	3.21	6900	1760	5137.98	2938.27	2199.71	3,700	3,900	13,800	8,210
5.7L V8 HEMI	A8 8HP70	3.92	6900	1760	5137.98	2938.27	2199.71	3,700	3,900	15,950	10,360
3.0L V6 ECODIESEL	A8 8HP70	3.55	6950	1600	5349.84	3129.89	2219.95	3,700	3,900	13,750	7,990
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1600	5349.84	3129.89	2219.95	3,700	3,900	13,750	7,990
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1600	5349.84	3129.89	2219.95	3,700	3,900	14,750	8,990
QUAD CAB - 6'4" Box 4x4											
3.6L V6	A8 845RE	3.21	6800	1710	5094.16	2905.80	2188.36	3,900	3,900	9,850	4,410
3.6L V6	A8 845RE	3.55	6800	1710	5094.16	2905.80	2188.36	3,900	3,900	12,900	7,400
5.7L V8 HEMI	A6 65RFE	3.55	6900	1590	5313.35	3134.51	2178.84	3,900	3,900	14,400	8,710
5.7L V8 HEMI	A6 65RFE	3.92	6900	1590	5313.35	3134.51	2178.84	3,900	3,900	15,950	10,260
5.7L V8 HEMI	A8 8HP70	3.21	6900	1580	5321.42	3128.11	2193.31	3,900	3,900	13,800	8,050
5.7L V8 HEMI	A8 8HP70	3.92	6900	1580	5321.42	3128.11	2193.31	3,900	3,900	15,950	10,200
3.0L V6 ECODIESEL	A8 8HP70	3.55	6950	1390	5560.14	3307.21	2252.93	3,900	3,900	13,750	7,750
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1390	5560.14	3307.21	2252.93	3,900	3,900	13,750	7,750
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1390	5560.14	3307.21	2252.93	3,900	3,900	14,750	8,750

- 1 Payload and Max Trailer Weights are ESTIMATED values.
- 2 All weights are shown in pounds unless otherwise stated.
- 3 Payload and Max Trailer Weight values are rounded to the nearest 10 lb.
- 4 Payload = GVWR – Base Weight.
- 5 Trailer Weight Rating and Tow Vehicle Trailering Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb.
 Options Weight is option content above 33 percent of sales volume.
 Trailer equipment weight =
 Class IV receiver hitch is 11.1 lb (if not already included in options weight).
 Trailer Hitch is 10 lb if TWR is less or equal to 5,000 lb and 65 lb if TWR is greater than 5,000 lb.
- 6 Payload and Trailer Weight Rating are mutually exclusive.
- 7 GAWRs, GVWRs and GCWRs should never be exceeded.
- 8 The recommended tongue weight for a conventional hitch is 10 percent of the gross trailer weight. The maximum tongue weight for Class IV receiver hitch is limited to 1100 lb.
- 9 Weight Distributing Hitch is recommended for trailers over 5,000 lb.
- 10 Quad Cab and Crew Cab models with Off Road Tire (s/c TXN), All Terrain Tire (s/c TWG) or Steel Wheel (s/c WFP) have 6800 lb GVWR.
- 11 All models with 22 inch Tires (s/c TY4) have 6200 lb GVWR.
- 12 Big Horn and Lone Star packages equipped with the 3.0L V6 EcoDiesel Engine and a 3.92 axle ratio have 13,750 lb. GCWR.

2016 RAM 1500 Trailer Towing Chart - SAE J2807 Compliant											
Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
CREW CAB - 5'7" Box, 4x2											
3.6L V6	A8 845RE	3.21	6800	1830	4973.19	2747.56	2225.63	3,700	3,900	9,850	4,480
3.6L V6	A8 845RE	3.55	6800	1830	4973.19	2747.56	2225.63	3,700	3,900	12,900	7,470
5.7L V8 HEMI	A6 65RFE	3.21	6900	1700	5196.50	2965.11	2231.39	3,700	3,900	12,350	6,760
5.7L V8 HEMI	A6 65RFE	3.55	6900	1700	5196.50	2965.11	2231.39	3,700	3,900	14,400	8,810
5.7L V8 HEMI	A6 65RFE	3.92	6900	1700	5196.50	2965.11	2231.39	3,700	3,900	15,950	10,360
5.7L V8 HEMI	A8 8HP70	3.21	6900	1690	5211.88	2979.36	2232.52	3,700	3,900	13,800	8,150
5.7L V8 HEMI	A8 8HP70	3.92	6900	1690	5211.88	2979.36	2232.52	3,700	3,900	15,950	10,300
3.0L V6 ECODIESEL	A8 8HP70	3.55	6950	1540	5409.51	3131.79	2277.72	3,700	3,900	13,750	7,870
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1540	5409.51	3131.79	2277.72	3,700	3,900	13,750	7,870
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1540	5409.51	3131.79	2277.72	3,700	3,900	14,750	8,870
CREW CAB - 5'7" Box, 4x4											
3.6L V6	A8 845RE	3.21	6800	1640	5163.52	2916.56	2246.96	3,900	3,900	9,850	4,170
3.6L V6	A8 845RE	3.55	6800	1640	5163.52	2916.56	2246.96	3,900	3,900	12,900	7,160
3.6L V6	A8 845RE	3.92	6800	1640	5163.52	2916.56	2246.96	3,900	3,900	12,900	7,160
5.7L V8 HEMI	A6 65RFE	3.55	6900	1540	5364.97	3124.07	2240.90	3,900	3,900	14,400	8,640
5.7L V8 HEMI	A6 65RFE	3.92	6900	1540	5364.97	3124.07	2240.90	3,900	3,900	15,950	10,190
5.7L V8 HEMI	A8 8HP70	3.21	6900	1520	5380.62	3143.87	2236.75	3,900	3,900	13,800	8,010
5.7L V8 HEMI	A8 8HP70	3.92	6900	1520	5380.62	3143.87	2236.75	3,900	3,900	15,950	10,160
3.0L V6 ECODIESEL	A8 8HP70	3.55	6950	1330	5623.58	3314.19	2309.39	3,900	3,900	13,750	7,610
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1330	5623.58	3314.19	2309.39	3,900	3,900	13,750	7,610
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1330	5623.58	3314.19	2309.39	3,900	3,900	14,750	8,610

- 1 Payload and Max Trailer Weights are ESTIMATED values.
- 2 All weights are shown in pounds unless otherwise stated.
- 3 Payload and Max Trailer Weight values are rounded to the nearest 10 lb.
- 4 Payload = GVWR – Base Weight.
- 5 Trailer Weight Rating and Tow Vehicle Trailering Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb.
 Options Weight is option content above 33 percent of sales volume.
 Trailer equipment weight =
 Class IV receiver hitch is 11.1 lb (if not already included in options weight).
 Trailer Hitch is 10 lb if TWR is less or equal to 5,000 lb and 65 lb if TWR is greater than 5,000 lb.
- 6 Payload and Trailer Weight Rating are mutually exclusive.
- 7 GAWRs, GVWRs and GCWRs should never be exceeded.
- 8 The recommended tongue weight for a conventional hitch is 10 percent of the gross trailer weight. The maximum tongue weight for Class IV receiver hitch is limited to 1100 lb.
- 9 Weight Distributing Hitch is recommended for trailers over 5,000 lb.
- 10 Quad Cab and Crew Cab models with Off Road Tire (s/c TXN), All Terrain Tire (s/c TWG) or Steel Wheel (s/c WFP) have 6800 lb GVWR.
- 11 All models with 22 inch Tires (s/c TY4) have 6200 lb GVWR.
- 12 Big Horn and Lone Star packages equipped with the 3.0L V6 EcoDiesel Engine and a 3.92 axle ratio have 13,750 lb. GCWR.

2016 RAM 1500 Trailer Towing Chart - SAE J2807 Compliant												
Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating	
					Total	Front	Rear	Front	Rear			
CREW CAB - 6'4" Box, 4x2												
5.7L V8 HEMI	A6 65RFE	3.21	6900	1690	5210.74	3032.33	2178.41	3,700	3,900	12,350	6,730	
5.7L V8 HEMI	A6 65RFE	3.55	6900	1690	5210.74	3032.33	2178.41	3,700	3,900	14,400	8,780	
5.7L V8 HEMI	A6 65RFE	3.92	6900	1690	5210.74	3032.33	2178.41	3,700	3,900	15,950	10,330	
5.7L V8 HEMI	A8 8HP70	3.21	6900	1650	5253.37	3046.35	2207.02	3,700	3,900	13,800	8,080	
5.7L V8 HEMI	A8 8HP70	3.92	6900	1650	5253.37	3046.35	2207.02	3,700	3,900	15,950	10,230	
CREW CAB - 6'4" Box, 4x4												
5.7L V8 HEMI	A6 65RFE	3.55	6900	1500	5402.56	3127.11	2275.45	3,900	3,900	14,400	8,540	
5.7L V8 HEMI	A6 65RFE	3.92	6900	1500	5402.56	3127.11	2275.45	3,900	3,900	15,950	10,090	
5.7L V8 HEMI	A8 8HP70	3.21	6900	1460	5444.57	3225.87	2218.70	3,900	3,900	13,800	7,780	
5.7L V8 HEMI	A8 8HP70	3.92	6900	1460	5444.57	3225.87	2218.70	3,900	3,900	15,850	9,830	
3.0L V6 ECODIESEL	A8 8HP70	3.55	6950	1260	5688.07	3377.23	2310.84	3,900	3,900	13,750	7,540	
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1260	5688.07	3377.23	2310.84	3,900	3,900	13,750	7,540	
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1260	5688.07	3377.23	2310.84	3,900	3,900	14,550	8,340	

- 1 Payload and Max Trailer Weights are ESTIMATED values.
- 2 All weights are shown in pounds unless otherwise stated.
- 3 Payload and Max Trailer Weight values are rounded to the nearest 10 lb.
- 4 Payload = GVWR – Base Weight.
- 5 Trailer Weight Rating and Tow Vehicle Trailering Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb.
 Options Weight is option content above 33 percent of sales volume.
 Trailer equipment weight =
 Class IV receiver hitch is 11.1 lb (if not already included in options weight).
 Trailer Hitch is 10 lb if TWR is less or equal to 5,000 lb and 65 lb if TWR is greater than 5,000 lb.
- 6 Payload and Trailer Weight Rating are mutually exclusive.
- 7 GAWRs, GVWRs and GCWRs should never be exceeded.
- 8 The recommended tongue weight for a conventional hitch is 10 percent of the gross trailer weight. The maximum tongue weight for Class IV receiver hitch is limited to 1100 lb.
- 9 Weight Distributing Hitch is recommended for trailers over 5,000 lb.
- 10 Quad Cab and Crew Cab models with Off Road Tire (s/c TXN), All Terrain Tire (s/c TWG) or Steel Wheel (s/c WFP) have 6800 lb GVWR.
- 11 All models with 22 inch Tires (s/c TY4) have 6200 lb GVWR.
- 12 Big Horn and Lone Star packages equipped with the 3.0L V6 EcoDiesel Engine and a 3.92 axle ratio have 13,750 lb. GCWR.