

	Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR			Max
						Total	Front	Rear	Front	Rear	GCWR	Trailer
	REGULAR CAB 4x2 TRADESMAN W BOX 8'0" SRW											
	6.7L I6 CUMMINS DIESEL	6-SPD AUTO 68RFE	3.73	11,500	4,610	6,886	4,220	2,666	5,500	7,000	28,300	20,940
	REGULAR CAB 4x2 TRADESMAN W BOX 8'0" DRW											
	6.7L I6 CUMMINS DIESEL	6-SPD AUTO 68RFE	3.73	14,000	6,840	7,163	4,218	2,945	5,500	9,750	28,300	20,670
	6.7L I6 CUMMINS DIESEL	6-SPD AUTO 68RFE	4.10	14,000	6,840	7,163	4,218	2,945	5,500	9,750	30,300	22,670
	CREW CAB 4x2 TRADESMAN W RAMBOX 6'4" SRW											
4x2	6.7L I6 CUMMINS DIESEL	6-SPD AUTO 68RFE	3.73	11,500	4,040	7,459	4,447	3,011	5,500	7,000	28,300	20,370
4	CREW CAB 4x2 TRADESMAN W BOX 6'4" SRW											
	6.7L I6 CUMMINS DIESEL	6-SPD AUTO 68RFE	3.73	11,500	4,190	7,313	4,425	2,888	5,500	7,000	28,300	20,520
	CREW CAB 4x2 TRADESMAN W BOX 8'0" SRW											
	6.7L I6 CUMMINS DIESEL	6-SPD AUTO 68RFE	3.73	12,000	4,540	7,456	4,562	2,894	5,500	7,000	28,300	20,370
	CREW CAB 4x2 TRADESMAN W BOX 8'0" DRW											
	6.7L I6 CUMMINS DIESEL	6-SPD AUTO 68RFE	3.73	14,000	6,190	7,814	4,561	3,253	5,500	9,750	28,300	20,020
	6.7L I6 CUMMINS DIESEL	6-SPD AUTO 68RFE	4.10	14,000	6,190	7,814	4,561	3,253	5,500	9,750	30,300	22,020

**10/28/2020** Page 1 of 3



	Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR			Max	
						Total	Front	Rear	Front	Rear	GCWR	Trailer	
	MEGA CAB 4x4 BIG HORN W BOX 6'4" SRW												
	6.7L I6 CUMMINS DIESEL	6-SPD AUTO 68RFE	3.73	12,300	4,300	7,999	4,897	3,102	6,000	7,000	28,300	19,830	
	MEGA CAB 4x4 BIG HORN W BOX 6'4" DRW												
	6.7L I6 CUMMINS DIESEL	6-SPD AUTO 68RFE	3.73	14,000	5,670	8,328	4,869	3,459	6,000	9,750	28,300	19,500	
	6.7L I6 CUMMINS DIESEL	6-SPD AUTO 68RFE	4.10	14,000	5,670	8,328	4,869	3,459	6,000	9,750	30,300	21,500	
	MEGA CAB 4x4 BIG HORN W RAMBOX 6'4" SRW												
	6.7L I6 CUMMINS DIESEL	6-SPD AUTO 68RFE	3.73	12,300	4,120	8,183	4,946	3,237	6,000	7,000	28,300	19,650	
	REGULAR CAB 4x4 TRADESMAN W BOX 8'0" DRW												
	6.7L I6 CUMMINS DIESEL	6-SPD AUTO 68RFE	3.73	14,000	6,400	7,597	4,533	3,064	6,000	9,750	28,300	20,230	
	6.7L I6 CUMMINS DIESEL	6-SPD AUTO 68RFE	4.10	14,000	6,400	7,597	4,533	3,064	6,000	9,750	30,300	22,230	
4×4	REGULAR CAB 4x4 TRADESMAN W BOX 8'0" SRW												
1	6.7L I6 CUMMINS DIESEL	6-SPD AUTO 68RFE	3.73	11,800	4,520	7,279	4,545	2,734	6,000	7,000	28,300	20,550	
	CREW CAB 4x4 TRADESMA	N W RAMBOX 6'4" SRW											
	6.7L I6 CUMMINS DIESEL	6-SPD AUTO 68RFE	3.73	11,800	4,060	7,743	4,684	3,059	6,000	7,000	28,300	20,090	
	CREW CAB 4x4 TRADESMAN W BOX 6'4" SRW												
	6.7L I6 CUMMINS DIESEL	6-SPD AUTO 68RFE	3.73	11,800	4,200	7,598	4,686	2,912	6,000	7,000	28,300	20,230	
	CREW CAB 4x4 TRADESMA												
	6.7L I6 CUMMINS DIESEL	6-SPD AUTO 68RFE	3.73	12,300	4,500	7,802	4,849	2,953	6,000	7,000	28,300	20,030	
	CREW CAB 4x4 TRADESMAN W BOX 8'0" DRW												
	6.7L I6 CUMMINS DIESEL	6-SPD AUTO 68RFE	3.73	14,000	5,860	8,142	4,855	3,287	6,000	9,750	28,300	19,690	
	6.7L I6 CUMMINS DIESEL	6-SPD AUTO 68RFE	4.10	14,000	5,860	8,142	4,855	3,287	6,000	9,750	30,300	21,690	

2021 Ram 3500 (D2) 6.7L SO Base Weight GCW Trailer Tow



		Avda				Base Weight		GAWR			May
Engine	Transmission	Axle Ratio	GVWR	Payload	Total	Front	Rear	Front	Rear	GCWR	Max Trailer

- Payload and Max Trailer Weights are ESTIMATED values.
- 2. All values are shown in pounds unless otherwise stated.
- 3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
- 4. Payload = GVWR Base Weight
- 5. Payload and Trailer Weight Rating are mutually exclusive.
- GAWRs, GVWRs and GCWRs should never be exceeded.
- 7. Trailer Weight Rating and Tow Vehicle Trailering Weight are calculated as specified in SAE J2807.

Passenger Weight = 300 lb

Options Weight = 100 lb

Trailering Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.

Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for a 5th Wheel or Gooseneck hitch.

Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailering equipment and tongue weight.

Box Off Body Completion Weight = 80 lb per foot from end of cab to end of fram

- 8. A fifth-wheel hitch is required for trailers over 23,000 lbs.
- A Gooseneck hitch is required for trailers over 30,000 lbs.