



	Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
						Total	Front	Rear	Front	Rear		
4x2	REGULAR CAB - CA 60" - 4X2 - DRW											
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	11,140	6,862	3,750	3,112	6,000 / 6,500	13,500	26,000	18,990
	6.4L V8 HEMI	A6 AS66RC	4.89	19,000	12,140	6,862	3,750	3,112	6,000 / 6,500	13,500	28,500	21,490
	REGULAR CAB - CA 84" - 4X2 - DRW											
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	11,010	6,988	3,890	3,098	6,000 / 6,500	13,500	26,000	18,860
	6.4L V8 HEMI	A6 AS66RC	4.89	19,500	12,510	6,988	3,890	3,098	6,000 / 6,500	13,500	28,500	21,360
	REGULAR CAB - CA 108" - 4X2 - DRW											
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	10,840	7,160	4,031	3,129	6,500 / 7,000	13,500	26,000	18,690
	6.4L V8 HEMI	A6 AS66RC	4.89	19,500	12,340	7,160	4,031	3,129	6,500 / 7,000	13,500	28,500	21,190
	REGULAR CAB - CA 120" - 4X2 - DRW											
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	10,790	7,212	4,076	3,136	6,500 / 7,000	13,500	26,000	18,640
	6.4L V8 HEMI	A6 AS66RC	4.89	19,500	12,290	7,212	4,076	3,136	6,500 / 7,000	13,500	28,500	21,140
	CREW CAB - CA 60" - 4X2 - DRW											
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	10,630	7,369	4,033	3,336	6,000 / 7,000	13,500	26,000	18,480
	6.4L V8 HEMI	A6 AS66RC	4.89	19,000	11,630	7,369	4,033	3,336	6,000 / 7,000	13,500	28,500	20,980
	CREW CAB - CA 84" - 4X2 - DRW											
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	10,440	7,562	4,211	3,351	6,000 / 7,000	13,500	26,000	18,290
	6.4L V8 HEMI	A6 AS66RC	4.89	19,500	11,940	7,562	4,211	3,351	6,000 / 7,000	13,500	28,500	20,790

Notes	Payload and Max Trailer Weights are ESTIMATED values	Indicates Max Payload/Trailer option (NOTE 4x2 or 4x4)
	All values are shown in pounds unless otherwise stated	
	Payload and Max Trailer Weight values are rounded to the nearest 10 lbs	
	Payload = GVWR - Base Weight	
	GAWRs, GVWRs, and GCWRs should never be exceeded	
	Recommended tongue weight determined by class hitch receiver and hardware limits of upfit	
	Upfit or Aftermarket equipment weight not included in Base Weight	

2020 RAM 5500 (DP) BASE WEIGHT GCW AND TRAILER TOW




	Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
						Total	Front	Rear	Front	Rear		
4x4	REGULAR CAB - CA 60" - 4X4 - DRW											
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	10,770	7,234	4,049	3,185	6,000 / 6,500	13,500	26,000	18,620
	6.4L V8 HEMI	A6 AS66RC	4.89	19,000	11,770	7,234	4,049	3,185	6,000 / 6,500	13,500	28,500	21,120
	REGULAR CAB - CA 84" - 4X4 - DRW											
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	10,630	7,366	4,215	3,151	6,000 / 6,500	13,500	26,000	18,480
	6.4L V8 HEMI	A6 AS66RC	4.89	19,500	12,130	7,366	4,215	3,151	6,000 / 6,500	13,500	28,500	20,980
	REGULAR CAB - CA 108" - 4X4 - DRW											
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	10,490	7,510	4,349	3,161	6,500 / 7,000	13,500	26,000	18,340
	6.4L V8 HEMI	A6 AS66RC	4.89	19,500	11,990	7,510	4,349	3,161	6,500 / 7,000	13,500	28,500	20,840
	REGULAR CAB - CA 120" - 4X4 - DRW											
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	10,410	7,588	4,410	3,178	6,500 / 7,000	13,500	26,000	18,260
	6.4L V8 HEMI	A6 AS66RC	4.89	19,500	11,910	7,588	4,410	3,178	6,500 / 7,000	13,500	28,500	20,760
	CREW CAB - CA 60" - 4X4 - DRW											
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	10,250	7,750	4,364	3,386	6,000 / 7,000	13,500	26,000	18,100
	6.4L V8 HEMI	A6 AS66RC	4.89	19,000	11,250	7,750	4,364	3,386	6,000 / 7,000	13,500	28,500	20,600
	CREW CAB - CA 84" - 4X4 - DRW											
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	10,080	7,920	4,530	3,390	6,000 / 7,000	13,500	26,000	17,930
	6.4L V8 HEMI	A6 AS66RC	4.89	19,500	11,580	7,920	4,530	3,390	6,000 / 7,000	13,500	28,500	20,430

Notes	Payload and Max Trailer Weights are ESTIMATED values ■ Indicates Max Payload/Trailer option (NOTE 4x2 or 4x4) All values are shown in pounds unless otherwise stated Payload and Max Trailer Weight values are rounded to the nearest 10 lbs Payload = GVWR - Base Weight GAWRs, GVWRs, and GCWRs should never be exceeded Recommended tongue weight determined by class hitch receiver and hardware limits of upfit Upfit or Aftermarket equipment weight not included in Base Weight
-------	---

2020 RAM 5500 (DP) BASE WEIGHT GCW AND TRAILER TOW



	Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
						Total	Front	Rear	Front	Rear		
4x2	REGULAR CAB - CA 60" - 4X2 - DRW											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	11,870	7,629	4,498	3,131	7,000 / 7,250	13,500	32,000	24,220
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	11,870	7,629	4,498	3,131	7,000 / 7,250	13,500	43,000	35,220
	REGULAR CAB - CA 84" - 4X2 - DRW											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	11,750	7,754	4,568	3,186	7,000 / 7,250	13,500	32,000	24,100
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	11,750	7,754	4,568	3,186	7,000 / 7,250	13,500	43,000	35,100
	REGULAR CAB - CA 108" - 4X2 - DRW											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	11,660	7,839	4,609	3,230	7,000 / 7,250	13,500	32,000	24,010
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	11,660	7,839	4,609	3,230	7,000 / 7,250	13,500	43,000	35,010
	REGULAR CAB - CA 120" - 4X2 - DRW											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	11,570	7,929	4,654	3,275	7,000 / 7,250	13,500	32,000	23,920
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	11,570	7,929	4,654	3,275	7,000 / 7,250	13,500	43,000	34,920
	CREW CAB - CA 60" - 4X2 - DRW											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	11,290	8,210	4,751	3,459	7,000 / 7,250	13,500	32,000	23,640
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	11,290	8,210	4,751	3,459	7,000 / 7,250	13,500	43,000	34,640
	CREW CAB - CA 84" - 4X2 - DRW											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	11,100	8,403	4,929	3,474	7,000 / 7,250	13,500	32,000	23,450
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	11,100	8,403	4,929	3,474	7,000 / 7,250	13,500	43,000	34,450

Notes	Payload and Max Trailer Weights are ESTIMATED values All values are shown in pounds unless otherwise stated Payload and Max Trailer Weight values are rounded to the nearest 10 lbs Payload = GVWR - Base Weight GAWRs, GVWRs, and GCWRs should never be exceeded Recommended tongue weight determined by class hitch receiver and hardware limits of upfit Upfit or Aftermarket equipment weight not included in Base Weight	 Indicates Max Payload/Trailer option (NOTE 4x2 or 4x4)
-------	---	--

2020 RAM 5500 (DP) BASE WEIGHT GCW AND TRAILER TOW



	Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
						Total	Front	Rear	Front	Rear		
4x4	REGULAR CAB - CA 60" - 4X4 - DRW											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	11,450	8,047	4,748	3,299	7,000 / 7,250	13,500	32,000	23,800
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	11,450	8,047	4,748	3,299	7,000 / 7,250	13,500	43,000	34,800
	REGULAR CAB - CA 84" - 4X4 - DRW											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	11,320	8,179	4,914	3,265	7,000 / 7,250	13,500	32,000	23,670
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	11,320	8,179	4,914	3,265	7,000 / 7,250	13,500	43,000	34,670
	REGULAR CAB - CA 108" - 4X4 - DRW											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	11,180	8,323	5,048	3,275	7,000 / 7,250	13,500	32,000	23,530
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	11,180	8,323	5,048	3,275	7,000 / 7,250	13,500	43,000	34,530
	REGULAR CAB - CA 120" - 4X4 - DRW											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	11,100	8,401	5,109	3,292	7,000 / 7,250	13,500	32,000	23,450
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	11,100	8,401	5,109	3,292	7,000 / 7,250	13,500	43,000	34,450
	CREW CAB - CA 60" - 4X4 - DRW											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	10,940	8,563	5,063	3,500	7,000 / 7,250	13,500	32,000	23,290
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	10,940	8,563	5,063	3,500	7,000 / 7,250	13,500	43,000	34,290
	CREW CAB - CA 84" - 4X4 - DRW											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	10,770	8,733	5,229	3,504	7,000 / 7,250	13,500	32,000	23,120
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	10,770	8,733	5,229	3,504	7,000 / 7,250	13,500	43,000	34,120

Notes	Payload and Max Trailer Weights are ESTIMATED values Indicates Max Payload/Trailer option (NOTE 4x2 or 4x4) All values are shown in pounds unless otherwise stated Payload and Max Trailer Weight values are rounded to the nearest 10 lbs Payload = GVWR - Base Weight GAWRs, GVWRs, and GCWRs should never be exceeded Recommended tongue weight determined by class hitch receiver and hardware limits of upfit Upfit or Aftermarket equipment weight not included in Base Weight
-------	--

2020 RAM 5500 (DP) BASE WEIGHT GCW AND TRAILER TOW