

## 2018 Ram 2500 Trailer Towing Chart – SAE J2807 Compliant

Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
<b>REG CAB, LONG BOX, 4X2</b>											
5.7L V8 HEMI	A6 66RFE	3.73	9,000	3,050	5,952	3,366	2,586	5,000	6,000	18,300	11,880
5.7L V8 HEMI	A6 66RFE	4.10	9,000	3,050	5,952	3,366	2,586	5,000	6,000	20,300	13,880
6.4L V8 HEMI	A6 66RFE	3.73	10,000	3,990	6,014	3,429	2,585	5,500	6,000	19,800	13,320
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,990	6,014	3,429	2,585	5,500	6,000	22,800	16,320
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	10,000	3,060	6,943	4,247	2,696	5,500	6,000	24,300	16,890
6.7L CUMMINS DIESEL	A6 68RFE	3.42	10,000	3,160	6,844	4,171	2,673	5,500	6,000	25,300	17,980
<b>REG CAB LONG BOX 4X2 CNG</b>											
5.7L V8 CNG	A6 66RFE	3.73	9,200	2,350	6,854	3,685	3,169	5,000	6,000	15,000	7,680
<b>REG CAB, LONG BOX, 4X2, CANADA ONLY</b>											
6.4L V8 HEMI	A6 66RFE	3.73	9,900	3,890	6,014	3,429	2,585	5,500	6,000	19,800	13,320
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,890	6,014	3,429	2,585	5,500	6,000	22,800	16,320
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	9,900	2,960	6,943	4,247	2,696	5,500	6,000	24,300	16,880
6.7L CUMMINS DIESEL	A6 68RFE	3.42	9,900	3,060	6,844	4,171	2,673	5,500	6,000	25,300	17,980
<b>REG CAB, LONG BOX, 4X4</b>											
5.7L V8 HEMI	A6 66RFE	3.73	9,000	2,690	6,310	3,658	2,652	5,250	6,000	18,300	11,520
5.7L V8 HEMI	A6 66RFE	4.10	9,000	2,690	6,310	3,658	2,652	5,250	6,000	20,300	13,520
6.4L V8 HEMI	A6 66RFE	3.73	10,000	3,610	6,391	3,711	2,680	5,500	6,000	19,800	12,940
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,610	6,391	3,711	2,680	5,500	6,000	22,800	15,940
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	10,000	2,630	7,367	4,609	2,758	5,750	6,000	24,300	16,430
6.7L CUMMINS DIESEL	A6 68RFE	3.42	10,000	2,720	7,280	4,538	2,742	5,750	6,000	25,300	17,500
<b>REG CAB LONG BOX 4X4 CNG</b>											
5.7L V8 CNG	A6 665RFE	3.73	9,200	1,970	7,235	3,989	3,246	5,500	6,000	15,000	7,300
<b>REG CAB, LONG BOX, 4X4, CANADA ONLY</b>											
6.4L V8 HEMI	A6 66RFE	3.73	9,900	3,500	6,403	3,719	2,684	5,500	6,000	19,800	12,930
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,500	6,403	3,719	2,684	5,500	6,000	22,800	15,930
6.7L CUMMINS DIESEL	A6 68RFE	3.42	9,900	2,610	7,286	4,542	2,745	5,750	6,000	25,300	17,490
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	9,900	2,530	7,373	4,613	2,761	5,750	6,000	24,300	16,420

1. Payload and Max Trailer Weights are ESTIMATED values
2. All values are shown in pounds unless otherwise stated
3. Payload and Max Trailer Weight values are rounded to the nearest 10 lbs
4. Payload = GVWR - Base Weight
5. GAWRs, GVWRs, and GCWRs should never be exceeded
6. Recommended tongue weight determined by class hitch receiver and hardware limits of upfit
7. Upfit or Aftermarket equipment weight not included in Base Weight

**2018 Ram 2500 Trailer Towing Chart – SAE J2807 Compliant**

Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
<b>CREW CAB, SHORT BOX, 4X2</b>											
5.7L V8 HEMI	A6 66RFE	3.73	9,000	2,690	6,308	3,529	2,779	5,000	6,000	18,300	11,520
5.7L V8 HEMI	A6 66RFE	4.10	9,000	2,690	6,308	3,529	2,779	5,000	6,000	20,300	13,520
6.4L V8 HEMI	A6 66RFE	3.73	10,000	3,610	6,391	3,583	2,808	5,500	6,000	19,800	12,940
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,610	6,391	3,583	2,808	5,500	6,000	22,800	15,940
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	10,000	2,610	7,393	4,508	2,885	5,500	6,500	24,300	16,410
6.7L CUMMINS DIESEL	A6 68RFE	3.42	10,000	2,670	7,330	4,450	2,881	5,500	6,500	25,300	17,450
<b>CREW CAB, SHORT BOX, 4X2, CANADA ONLY</b>											
6.4L V8 HEMI	A6 66RFE	3.73	9,900	3,510	6,391	3,583	2,808	5,500	6,000	19,800	12,940
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,510	6,391	3,583	2,808	5,500	6,000	22,800	15,940
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	9,900	2,520	7,376	4,489	2,887	5,500	6,500	24,300	16,420
6.7L CUMMINS DIESEL	A6 68RFE	3.42	9,900	2,590	7,313	4,431	2,882	5,500	6,500	25,300	17,470
<b>CREW CAB, LONG BOX, 4X2</b>											
5.7L V8 HEMI	A6 66RFE	3.73	9,000	2,560	6,443	3,655	2,789	5,000	6,000	18,300	11,390
5.7L V8 HEMI	A6 66RFE	4.10	9,000	2,560	6,443	3,655	2,789	5,000	6,000	20,300	13,390
6.4L V8 HEMI	A6 66RFE	3.73	10,000	3,480	6,523	3,699	2,824	5,500	6,000	19,800	12,810
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,480	6,523	3,699	2,824	5,500	6,000	22,800	15,810
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	10,000	2,470	7,528	4,630	2,898	5,500	6,500	24,300	16,270
6.7L CUMMINS DIESEL	A6 68RFE	3.42	10,000	2,540	7,461	4,571	2,891	5,500	6,500	25,300	17,320
<b>CREW CAB LONG BOX 4X2 CNG</b>											
5.7L V8 CNG	A6 665RFE	3.73	9,200	1,850	7,353	3,851	3,502	5,000	6,000	15,000	7,180
<b>CREW CAB, LONG BOX, 4X2, CANADA ONLY</b>											
6.4L V8 HEMI	A6 66RFE	3.73	9,900	3,380	6,523	3,699	2,824	5,500	6,000	19,800	12,810
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,380	6,523	3,699	2,824	5,500	6,000	22,800	15,810
6.7L CUMMINS DIESEL	A6 68RFE	3.42	9,900	2,440	7,460	4,566	2,894	5,500	6,500	25,300	17,320
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	9,900	2,370	7,527	4,626	2,901	5,500	6,500	24,300	16,270
<b>CREW CAB, SHORT BOX, 4X4</b>											
5.7L V8 HEMI	A6 66RFE	3.73	9,000	2,350	6,648	3,813	2,835	5,250	6,000	18,300	11,180
5.7L V8 HEMI	A6 66RFE	4.10	9,000	2,350	6,648	3,813	2,835	5,250	6,000	20,300	13,180
6.4L V8 HEMI	A6 66RFE	3.73	10,000	3,300	6,701	3,857	2,844	5,500	6,000	19,800	12,630
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,300	6,701	3,857	2,844	5,500	6,000	22,800	15,630
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	10,000	2,310	7,685	4,761	2,924	5,750	6,000	24,300	16,110
6.7L CUMMINS DIESEL	A6 68RFE	3.42	10,000	2,380	7,619	4,700	2,918	5,750	6,000	25,300	17,160

### 2018 Ram 2500 Trailer Towing Chart – SAE J2807 Compliant

Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
<b>CREW CAB, SHORT BOX, 4X4, CANADA ONLY</b>											
6.4L V8 HEMI	A6 66RFE	3.73	9,900	3,200	6,700	3,862	2,838	5,500	6,000	19,800	12,630
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,200	6,700	3,862	2,838	5,500	6,000	22,800	15,630
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	9,900	2,200	7,701	4,765	2,936	5,750	6,000	24,300	16,090
6.7L CUMMINS DIESEL	A6 68RFE	3.42	9,900	2,270	7,634	4,704	2,930	5,750	6,000	25,300	17,140
<b>CREW CAB, LONG BOX, 4X4</b>											
5.7L V8 HEMI	A6 66RFE	3.73	9,000	2,180	6,819	3,958	2,860	5,250	6,000	18,300	11,010
5.7L V8 HEMI	A6 66RFE	4.10	9,000	2,180	6,819	3,958	2,860	5,250	6,000	20,300	13,010
6.4L V8 HEMI	A6 66RFE	3.73	10,000	3,140	6,862	3,995	2,867	5,500	6,000	19,800	12,470
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,140	6,862	3,995	2,867	5,500	6,000	22,800	15,470
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	10,000	2,130	7,869	4,912	2,957	5,750	6,000	24,300	15,920
6.7L CUMMINS DIESEL	A6 68RFE	3.42	10,000	2,200	7,799	4,848	2,950	5,750	6,000	25,300	16,750
<b>CREW CAB, LONG BOX, 4X4, CNG</b>											
5.7L V8 CNG	A6 66RFE	3.73	9,200	1,490	7,709	4,145	3,564	5,500	6,000	15,000	6,820
<b>CREW CAB LONG BOX 4X4 CANADA ONLY</b>											
6.4L V8 HEMI	A6 66RFE	3.73	9,900	3,030	6,868	3,998	2,870	5,500	6,000	19,800	12,460
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,030	6,868	3,998	2,870	5,500	6,000	22,800	15,460
6.7L CUMMINS DIESEL	A6 68RFE	3.42	9,900	2,100	7,804	4,851	2,953	5,750	6,000	25,300	15,690
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	9,900	2,030	7,875	4,915	2,960	5,750	6,000	24,300	15,140
<b>CREW CAB, SHORT BOX, 4X4, POWER WAGON</b>											
6.4L V8 HEMI	A6 66RFE	4.10	8,565	1,560	7,000	4,139	2,861	4,750	6,200	17,525	10,050

1. Payload and Max Trailer Weights are ESTIMATED values
2. All values are shown in pounds unless otherwise stated
3. Payload and Max Trailer Weight values are rounded to the nearest 10 lbs
4. Payload = GVWR - Base Weight
5. GAWRs, GVWRs, and GCWRs should never be exceeded
6. Recommended tongue weight determined by class hitch receiver and hardware limits of upfit
7. Upfit or Aftermarket equipment weight not included in Base Weight

### 2018 Ram 2500 Trailer Towing Chart – SAE J2807 Compliant

Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
<b>MEGA CA,B SHORT BOX, 4X2</b>											
5.7 GAS HEMI	A6 66RFE	3.73	9,000	2,210	6,787	3,754	3,033	5,000	6,200	18,300	11,040
5.7 GAS HEMI	A6 66RFE	4.10	9,000	2,210	6,787	3,754	3,033	5,000	6,200	20,300	13,040
6.4 GAS HEMI	A6 66RFE	3.73	10,000	3,180	6,818	3,795	3,023	5,500	6,500	19,800	12,510
6.4 GAS HEMI	A6 66RFE	4.10	10,000	3,180	6,818	3,795	3,023	5,500	6,500	22,800	15,510
6.7 DIESEL CUMMINS	M6 MT-G56	3.42	10,000	2,270	7,726	4,695	3,031	5,500	6,500	24,300	16,100
6.7 DIESEL CUMMINS	A6 68RFE	3.42	10,000	2,340	7,658	4,634	3,024	5,500	6,500	25,300	17,170
<b>MEGA CAB, SHORT BOX, 4X2, CANADA ONLY</b>											
6.4 GAS HEMI	A6 66RFE	3.73	9,900	3,090	6,807	3,777	3,030	5,500	6,500	19,800	12,520
6.4 GAS HEMI	A6 66RFE	4.10	9,900	3,090	6,807	3,777	3,030	5,500	6,500	22,800	15,520
6.7 DIESEL CUMMINS	M6 MT-G56	3.42	9,900	2,170	7,726	4,695	3,031	5,500	6,500	24,300	16,100
6.7 DIESEL CUMMINS	A6 68RFE	3.42	9,900	2,240	7,658	4,634	3,024	5,500	6,500	25,300	17,170
<b>MEGA CA,B SHORT BOX, 4X4</b>											
5.7 GAS HEMI	A6 66RFE	3.73	9,000	1,960	7,042	4,008	3,034	5,250	6,200	18,300	10,780
5.7 GAS HEMI	A6 66RFE	4.10	9,000	1,960	7,042	4,008	3,034	5,250	6,200	20,300	12,780
6.4 GAS HEMI	A6 66RFE	3.73	10,000	2,910	7,090	4,056	3,035	5,500	6,500	19,800	12,240
6.4 GAS HEMI	A6 66RFE	4.10	10,000	2,910	7,090	4,056	3,035	5,500	6,500	22,800	15,240
6.7 DIESEL CUMMINS	M6 MT-G56	3.42	10,000	1,950	8,050	4,954	3,096	6,000	6,500	24,300	14,750
6.7 DIESEL CUMMINS	A6 68RFE	3.42	10,000	2,020	7,982	4,892	3,090	6,000	6,500	25,300	15,430
<b>MEGA CAB, SHORT BOX, 4X4, CANADA ONLY</b>											
6.4 GAS HEMI	A6 66RFE	3.73	9,900	2,810	7,090	4,056	3,035	5,500	6,500	19,800	12,240
6.4 GAS HEMI	A6 66RFE	4.10	9,900	2,810	7,090	4,056	3,035	5,500	6,500	22,800	15,240
6.7 DIESEL CUMMINS	M6 MT-G56	3.42	9,900	1,850	8,050	4,954	3,096	6,000	6,500	24,300	13,750
6.7 DIESEL CUMMINS	A6 68RFE	3.42	9,900	1,920	7,982	4,892	3,090	6,000	6,500	25,300	14,430

1. Payload and Max Trailer Weights are ESTIMATED values
2. All values are shown in pounds unless otherwise stated
3. Payload and Max Trailer Weight values are rounded to the nearest 10 lbs
4. Payload = GVWR - Base Weight
5. GAWRs, GVWRs, and GCWRs should never be exceeded
6. Recommended tongue weight determined by class hitch receiver and hardware limits of upfit
7. Upfit or Aftermarket equipment weight not included in Base Weight

**2018 Ram 2500 Trailer Towing Chart – SAE J2807 Compliant**

Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		VECI Label		UVW	Max Upfit Weight	GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear	MCVW	Frontal Area (ft)				
<b>REG CAB, LONG BOX, 4X2 - BOX OFF</b>															
6.4L V8 HEMI	A6 66RFE	3.73	10,000	4,490	5,510	3,399	2,111	5,500	6,500	8,500	58	8,000	2,490	19,800	13,160
6.4L V8 HEMI	A6 66RFE	4.10	10,000	4,490	5,510	3,399	2,111	5,500	6,500	8,500	58	8,000	2,490	22,800	16,160
<b>REG CAB, LONG BOX, 4X2 - BOX OFF, CANADA ONLY</b>															
6.4L V8 HEMI	A6 66RFE	3.73	9,900	4,390	5,510	3,399	2,111	5,500	6,500	8,500	58	8,000	2,490	19,800	13,160
6.4L V8 HEMI	A6 66RFE	4.10	9,900	4,390	5,510	3,399	2,111	5,500	6,500	8,500	58	8,000	2,490	22,800	16,160
<b>REG CAB, LONG BOX, 4X4 - BOX OFF</b>															
6.4L V8 HEMI	A6 66RFE	3.73	10,000	4,100	5,901	3,763	2,139	5,500	6,500	8,500	58	8,000	2,099	19,800	12,770
6.4L V8 HEMI	A6 66RFE	4.10	10,000	4,100	5,901	3,763	2,139	5,500	6,500	8,500	58	8,000	2,099	22,800	15,770
<b>REG CAB, LONG BOX, 4X4 - BOX OFF, CANADA ONLY</b>															
6.4L V8 HEMI	A6 66RFE	3.73	9,900	4,000	5,898	3,689	2,210	5,500	6,500	8,500	58	8,000	2,102	19,800	12,780
6.4L V8 HEMI	A6 66RFE	4.10	9,900	4,000	5,898	3,689	2,210	5,500	6,500	8,500	58	8,000	2,102	22,800	15,780
<b>CREW CAB, SHORT BOX, 4X2 - BOX OFF</b>															
6.4L V8 HEMI	A6 66RFE	3.73	10,000	3,990	6,011	3,679	2,332	5,500	6,500	8,500	58	8,000	1,989	19,800	12,750
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,990	6,011	3,679	2,332	5,500	6,500	8,500	58	8,000	1,989	22,800	15,750
<b>CREW CAB, SHORT BOX, 4X2 - BOX OFF CANADA ONLY</b>															
6.4L V8 HEMI	A6 66RFE	3.73	9,900	3,890	6,011	3,679	2,332	5,500	6,500	8,500	58	8,000	1,989	19,800	12,750
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,890	6,011	3,679	2,332	5,500	6,500	8,500	58	8,000	1,989	22,800	15,750
<b>CREW CAB, LONG BOX, 4X2 - BOX OFF</b>															
6.4L V8 HEMI	A6 66RFE	3.73	10,000	3,950	6,049	3,727	2,322	5,500	6,500	8,500	58	8,000	1,951	19,800	12,640
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,950	6,049	3,727	2,322	5,500	6,500	8,500	58	8,000	1,951	22,800	15,640
<b>CREW CAB, LONG BOX, 4X2 - BOX OFF CANADA ONLY</b>															
6.4L V8 HEMI	A6 66RFE	3.73	9,900	3,850	6,049	3,727	2,322	5,500	6,500	8,500	58	8,000	1,951	19,800	12,640
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,850	6,049	3,727	2,322	5,500	6,500	8,500	58	8,000	1,951	22,800	15,640
<b>CREW CAB, SHORT BOX, 4X4 - BOX OFF</b>															
6.4L V8 HEMI	A6 66RFE	3.73	10,000	3,690	6,311	3,947	2,363	5,500	6,500	8,500	58	8,000	1,689	19,800	12,450
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,690	6,311	3,947	2,363	5,500	6,500	8,500	58	8,000	1,689	22,800	15,450
<b>CREW CAB, SHORT BOX, 4X4 - BOX OFF CANADA ONLY</b>															
6.4L V8 HEMI	A6 66RFE	3.73	9,900	3,590	6,311	3,947	2,363	5,500	6,500	8,500	58	8,000	1,689	19,800	12,450
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,590	6,311	3,947	2,363	5,500	6,500	8,500	58	8,000	1,689	22,800	15,450
<b>CREW CAB, LONG BOX, 4X4 - BOX OFF</b>															
6.4L V8 HEMI	A6 66RFE	3.73	10,000	3,590	6,408	4,020	2,389	5,500	6,500	8,500	58	8,000	1,592	19,800	12,280
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,590	6,408	4,020	2,389	5,500	6,500	8,500	58	8,000	1,592	22,800	15,280
<b>CREW CAB, LONG BOX, 4X4 - BOX OFF CANADA ONLY</b>															
6.4L V8 HEMI	A6 66RFE	3.73	9,900	3,470	6,425	3,989	2,436	5,500	6,500	8,500	58	8,000	1,575	19,800	12,260
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,470	6,425	3,989	2,436	5,500	6,500	8,500	58	8,000	1,575	22,800	15,260

1. Payload and Max Trailer Weights are ESTIMATED values
2. All values are shown in pounds unless otherwise stated
3. Payload and Max Trailer Weight values are rounded to the nearest 10 lbs
4. Payload = GVWR - Base Weight
5. GAWRs, GVWRs, and GCWRs should never be exceeded
6. Recommended tongue weight determined by class hitch receiver and hardware limits of upfit
7. Upfit or Aftermarket equipment weight not included in Base Weight
8. MCVW: Maximum Completed Vehicle Weight, includes Total Base Weight + permanently attached Upfit Weight
9. Frontal Area: Maximum allowable Frontal Area, in Ft<sup>2</sup>, that the vehicle can project. For details on calculations please refer to Ram Body Builders Guide.
10. VECI Label & Max Upfit Weight n/a: Vehicle is not restricted to MCVW, Frontal Area, or Maximum Upfit Weight limits, however GVWR/GAWR/GCWR cannot be exceeded.
11. UVW: Unloaded Vehicle Weight specified per FMVSS 301: Fuel System Integrity