

ST Model

4X4 Chassis Cab			FGAWR All		
Driver Only				Automatic	GVWR
8L63 Reg Cab	143.5"	6.7L TD Diesel	6,000	Available	14,000
8L63 Reg Cab	143.5"	6.4L HD HEMI	5,500	Available	14,000
8L63 Reg Cab	143.5"	6.4L HD HEMI	5,500	Available	13,500
8L64 Reg Cab	167.5"	6.7L TD Diesel	6,000	Available	14,000
8L64 Reg Cab	167.5"	6.4L HD HEMI	5,500	Available	14,000
8L64 Reg Cab	167.5"	6.4L HD HEMI	5,500	Available	13,500
8L93 Crew Cab	172.4"	6.7L TD Diesel	6,000	Available	14,000
8L93 Crew Cab	172.4"	6.4L HD HEMI	5,500	Available	14,000
8L93 Crew Cab	172.4"	6.4L HD HEMI	5,500	Available	13,500

ST Model

4X4 Chassis Cab			FGAWR All		
Driver Only				Automatic	GVWR
8L63 Reg Cab	143.5"	6.7L TD Diesel	6,000	Available	12,000
8L63 Reg Cab	143.5"	6.4L HD HEMI	5,500	Available	11,000
8L93 Crew Cab	172.4"	6.7L TD Diesel	6,000	Available	12,000
8L93 Crew Cab	172.4"	6.4L HD HEMI	5,500	Available	11,000

3500 Chassis Cab (DD) Snow Plow (AHD) Availability Chart

NOTE:

1. Minimum 700lb blade weight considered for plow availability.
2. Snowplow calculations are based upon maximum options, except for DRW Diesel Vehicles.
3. Single passenger weight = 150 lbs. (Driver Only).

CAUTION:

Many DRW models may require in excess of 1,000 lbs. of ballast behind the rear axle to ensure that the front axle is within GAWR. The GVWs, GAWRs, and base weights are provided in the technical information section to allow calculation of the appropriate ballast. Front and Rear GAWR should never be exceeded for all models with passengers and optional equipment.