

2017 VM RAM - PROMASTER CITY - TRAILER TOWING CHART J1

Engine	Transmission	Mkt	Axle Ratio	GVWR	Payload ¹	Base Weight			GAWR		GCWR ²	Max. Trailer Weight Rating ³
						Total	Front	Rear	Front	Rear		
2.4L I4 GASOLINE MULTIAIR ENGINE	9-SPD AUTO 948TE - DFH	USA-Cargo	3.73	5,395	1,883	3,512	2,213	1,299	2,690	2,866	5,900	2,000
2.4L I4 GASOLINE MULTIAIR ENGINE	9-SPD AUTO 948TE - DFH	USA-Wagon	3.73	5,395	1,713	3,682	2,320	1,362	2,690	2,866	5,900	1,867
2.4L I4 GASOLINE MULTIAIR ENGINE	9-SPD AUTO 948TE - DFH	CAN-Cargo	3.73	5,395	1,901	3,494	2,208	1,286	2,690	2,866	5,900	2,000
2.4L I4 GASOLINE MULTIAIR ENGINE	9-SPD AUTO 948TE - DFH	CAN-Wagon	3.73	5,395	1,713	3,682	2,320	1,362	2,690	2,866	5,900	1,867

Notes: Payload and Max Trailer weights are ESTIMATED values.

All values are shown in pounds unless otherwise stated

(1) Payload. (Payload = GVWR - Base Weight)

(2) GCWR is a defined value from Vehicle Engineering in lbs (max GCWR = 5,900 lbs)

(3) Max Trailer weight is limited to 2,000 lbs.

Payload and Maximum Trailer weight are mutually exclusive.

The recommended tongue weight is 10% of trailer weight.

Hitch rating, GAWRs, and GCWR should never be exceeded.