2016 VM RAM - PROMASTER CITY - TRAILER TOWING CHART - SAE J2807 COMPLIANT

Engine	Transmission	Mkt	Axle Ratio	GVWR	Payload [1]	Base Weight			GAWR		GCWR [2]	Max Trailer [3]
						Total	Front	Rear	Front	Rear		
2.4L I4 GASOLINE MULTIAIR ENGINE	9-SPD AUTO 948TE - DFH	USA-Cargo	3.73	5,395	1,883	3,512	2,213	1,299	2,690	2,866	5,900	2,000
2.4L I4 GASOLINE MULTIAIR ENGINE	9-SPD AUTO 948TE - DFH	USA-Wagon	3.73	5,395	1,713	3,682	2,319	1,363	2,690	2,866	5,900	1,867
2.4L I4 GASOLINE MULTIAIR ENGINE	9-SPD AUTO 948TE - DFH	CAN-Cargo	3.73	5,395	1,900	3,495	2,209	1,286	2,690	2,866	5,900	2,000
2.4L I4 GASOLINE MULTIAIR ENGINE	9-SPD AUTO 948TE - DFH	CAN-Wagon	3.73	5,395	1,713	3,682	2,319	1,363	2,690	2,866	5,900	1,867

Notes: Payload and Max Trailer weights are ESTIMATED values.
All values are shown in pounds unless otherwise stated
(1) Payload. (Payload = GVWR - Base Weight)
(2) GCWR is a defined valude from Chrysler Vehicle Engineering in lbs (max GCWR = 5,900 lbs)
(3) Max Trailer weight is limited to 2,000 lbs.
Payload and Maximum Trailer weight are mutually exclusive.
The recommended tongue weight is 10% of trailer weight.
Hitch rating, GAWRs, and GCWR should never be exceeded.