2017 RAM - Promaster City - Trailer Towing Chart - SAE J2807 compliant

Engine	Transmission	Mkt	Axle Ratio	GVWR	Payload [1]	Base Weight			GAWR		GCWR[2]	Max. Trailer Weight Rating[3]
						Total	Front	Rear	Front	Rear		
RAM Promaster City												
2.4L I4 GASOLINE MULTIAIR ENGINE	9-SPD AUTO 948TE - DFH	USA	3.73	5,395	1,883	3,512	2,213	1,299	2,690	2,866	5,900	2,000
2.4L I4 GASOLINE MULTIAIR ENGINE	9-SPD AUTO 948TE - DFH	CAN	3.73	5,395	1,901	3,494	2,208	1,286	2,690	2,866	5,900	2,000

1. Payload and Max Trailer weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated
3. (1) Payload. (Payload = GVWR - Base Weight)
4. (2) GCWR is a defined value from Vehicle Engineering in lbs (max GCWR = 5,900 lbs)
5. (3) Max Trailer weight is limited to 2,000 lbs.
6. Payload and Maximum Trailer weight are mutually exclusive.
7. Trailer Weight Rating and Tow Vehicle Trailering Weight are calculated as specified in SAE J2807.
Driver and passenger Weight = 300 lb.
Trailering Equipment Weight: 50.7 lb for Convencional Hitch.
8. The recommended tongue weight is 10% of trailer weight.
9. Hitch rating, GAWRs, and GCWR should never be exceeded.