

2018 Ram 2500 Trailer Towing Chart – SAE J2807 Compliant											
Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
REG CAB, LONG BOX, 4X2											
5.7L V8 HEMI	A6 66RFE	3.73	9,000	3,050	5,952	3,366	2,586	5,000	6,000	18,300	11,880
5.7L V8 HEMI	A6 66RFE	4.10	9,000	3,050	5,952	3,366	2,586	5,000	6,000	20,300	13,880
6.4L V8 HEMI	A6 66RFE	3.73	10,000	3,990	6,014	3,429	2,585	5,500	6,000	19,800	13,320
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,990	6,014	3,429	2,585	5,500	6,000	22,800	16,320
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	10,000	3,060	6,943	4,247	2,696	5,500	6,000	24,300	16,890
6.7L CUMMINS DIESEL	A6 68RFE	3.42	10,000	3,160	6,844	4,171	2,673	5,500	6,000	25,300	17,980
REG CAB LONG BOX 4X2 CNG											
5.7L V8 CNG	A6 66RFE	3.73	9,200	2,350	6,854	3,685	3,169	5,000	6,000	15,000	7,680
REG CAB, LONG BOX, 4X2, CANADA ONLY											
6.4L V8 HEMI	A6 66RFE	3.73	9,900	3,890	6,014	3,429	2,585	5,500	6,000	19,800	13,320
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,890	6,014	3,429	2,585	5,500	6,000	22,800	16,320
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	9,900	2,960	6,943	4,247	2,696	5,500	6,000	24,300	16,880
6.7L CUMMINS DIESEL	A6 68RFE	3.42	9,900	3,060	6,844	4,171	2,673	5,500	6,000	25,300	17,980
REG CAB, LONG BOX, 4X4											
5.7L V8 HEMI	A6 66RFE	3.73	9,000	2,690	6,310	3,658	2,652	5,250	6,000	18,300	11,520
5.7L V8 HEMI	A6 66RFE	4.10	9,000	2,690	6,310	3,658	2,652	5,250	6,000	20,300	13,520
6.4L V8 HEMI	A6 66RFE	3.73	10,000	3,610	6,391	3,711	2,680	5,500	6,000	19,800	12,940
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,610	6,391	3,711	2,680	5,500	6,000	22,800	15,940
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	10,000	2,630	7,367	4,609	2,758	5,750	6,000	24,300	16,430
6.7L CUMMINS DIESEL	A6 68RFE	3.42	10,000	2,720	7,280	4,538	2,742	5,750	6,000	25,300	17,500
REG CAB LONG BOX 4X4 CNG											
5.7L V8 CNG	A6 66RFE	3.73	9,200	1,970	7,235	3,989	3,246	5,500	6,000	15,000	7,300
REG CAB, LONG BOX, 4X4, CANADA ONLY											
6.4L V8 HEMI	A6 66RFE	3.73	9,900	3,500	6,403	3,719	2,684	5,500	6,000	19,800	12,930
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,500	6,403	3,719	2,684	5,500	6,000	22,800	15,930
6.7L CUMMINS DIESEL	A6 68RFE	3.42	9,900	2,610	7,286	4,542	2,745	5,750	6,000	25,300	17,490
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	9,900	2,530	7,373	4,613	2,761	5,750	6,000	24,300	16,420

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.

Passenger Weight = 300 lb

Options Weight = 100 lb

Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for 5th Wheel or Gooseneck hitch.

Trailing Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.

Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailing equipment and tongue weight.

Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.

8. The maximum tongue weight for Class V (receiver hitch) is limited to 1,800 lb.

9. Maximum Capability

2018 Ram 2500 Trailer Towing Chart – SAE J2807 Compliant												
Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating	
					Total	Front	Rear	Front	Rear			
CREW CAB, SHORT BOX, 4X2												
5.7L V8 HEMI	A6 66RFE	3.73	9,000	2,690	6,308	3,529	2,779	5,000	6,000	18,300	11,520	
5.7L V8 HEMI	A6 66RFE	4.10	9,000	2,690	6,308	3,529	2,779	5,000	6,000	20,300	13,520	
6.4L V8 HEMI	A6 66RFE	3.73	10,000	3,610	6,391	3,583	2,808	5,500	6,000	19,800	12,940	
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,610	6,391	3,583	2,808	5,500	6,000	22,800	15,940	
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	10,000	2,610	7,393	4,508	2,885	5,500	6,500	24,300	16,410	
6.7L CUMMINS DIESEL	A6 68RFE	3.42	10,000	2,670	7,330	4,450	2,881	5,500	6,500	25,300	17,450	
CREW CAB, SHORT BOX, 4X2, CANADA ONLY												
6.4L V8 HEMI	A6 66RFE	3.73	9,900	3,510	6,391	3,583	2,808	5,500	6,000	19,800	12,940	
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,510	6,391	3,583	2,808	5,500	6,000	22,800	15,940	
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	9,900	2,520	7,376	4,489	2,887	5,500	6,500	24,300	16,420	
6.7L CUMMINS DIESEL	A6 68RFE	3.42	9,900	2,590	7,313	4,431	2,882	5,500	6,500	25,300	17,470	
CREW CAB, LONG BOX, 4X2												
5.7L V8 HEMI	A6 66RFE	3.73	9,000	2,560	6,443	3,655	2,789	5,000	6,000	18,300	11,390	
5.7L V8 HEMI	A6 66RFE	4.10	9,000	2,560	6,443	3,655	2,789	5,000	6,000	20,300	13,390	
6.4L V8 HEMI	A6 66RFE	3.73	10,000	3,480	6,523	3,699	2,824	5,500	6,000	19,800	12,810	
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,480	6,523	3,699	2,824	5,500	6,000	22,800	15,810	
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	10,000	2,470	7,528	4,630	2,898	5,500	6,500	24,300	16,270	
6.7L CUMMINS DIESEL	A6 68RFE	3.42	10,000	2,540	7,461	4,571	2,891	5,500	6,500	25,300	17,320	
CREW CAB LONG BOX 4X2 CNG												
5.7L V8 CNG	A6 66SRFE	3.73	9,200	1,850	7,353	3,851	3,502	5,000	6,000	15,000	7,180	
CREW CAB, LONG BOX, 4X2, CANADA ONLY												
6.4L V8 HEMI	A6 66RFE	3.73	9,900	3,380	6,523	3,699	2,824	5,500	6,000	19,800	12,810	
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,380	6,523	3,699	2,824	5,500	6,000	22,800	15,810	
6.7L CUMMINS DIESEL	A6 68RFE	3.42	9,900	2,440	7,460	4,566	2,894	5,500	6,500	25,300	17,320	
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	9,900	2,370	7,527	4,626	2,901	5,500	6,500	24,300	16,270	

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.

Passenger Weight = 300 lb

Options Weight = 100 lb

Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for 5th Wheel or Gooseneck hitch.

Trailing Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.

Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailering equipment and tongue weight.

Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.

8. The maximum tongue weight for Class V (receiver hitch) is limited to 1,800 lb.

9. Maximum Capability

2018 Ram 2500 Trailer Towing Chart – SAE J2807 Compliant											
Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
CREW CAB, SHORT BOX, 4X4											
5.7L V8 HEMI	A6 66RFE	3.73	9,000	2,350	6,648	3,813	2,835	5,250	6,000	18,300	11,180
5.7L V8 HEMI	A6 66RFE	4.10	9,000	2,350	6,648	3,813	2,835	5,250	6,000	20,300	13,180
6.4L V8 HEMI	A6 66RFE	3.73	10,000	3,300	6,701	3,857	2,844	5,500	6,000	19,800	12,630
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,300	6,701	3,857	2,844	5,500	6,000	22,800	15,630
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	10,000	2,310	7,685	4,761	2,924	5,750	6,000	24,300	16,110
6.7L CUMMINS DIESEL	A6 68RFE	3.42	10,000	2,380	7,619	4,700	2,918	5,750	6,000	25,300	17,160
CREW CAB, SHORT BOX, 4X4, CANADA ONLY											
6.4L V8 HEMI	A6 66RFE	3.73	9,900	3,200	6,700	3,862	2,838	5,500	6,000	19,800	12,630
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,200	6,700	3,862	2,838	5,500	6,000	22,800	15,630
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	9,900	2,200	7,701	4,765	2,936	5,750	6,000	24,300	16,090
CREW CAB, LONG BOX, 4X4											
5.7L V8 HEMI	A6 66RFE	3.73	9,000	2,180	6,819	3,958	2,860	5,250	6,000	18,300	11,010
5.7L V8 HEMI	A6 66RFE	4.10	9,000	2,180	6,819	3,958	2,860	5,250	6,000	20,300	13,010
6.4L V8 HEMI	A6 66RFE	3.73	10,000	3,140	6,862	3,995	2,867	5,500	6,000	19,800	12,470
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,140	6,862	3,995	2,867	5,500	6,000	22,800	15,470
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	10,000	2,130	7,869	4,912	2,957	5,750	6,000	24,300	15,920
6.7L CUMMINS DIESEL	A6 68RFE	3.42	10,000	2,200	7,799	4,848	2,950	5,750	6,000	25,300	16,750
CREW CAB, LONG BOX, 4X4, CNG											
5.7L V8 CNG	A6 66RFE	3.73	9,200	1,490	7,709	4,145	3,564	5,500	6,000	15,000	6,820
CREW CAB LONG BOX 4X4 CANADA ONLY											
6.4L V8 HEMI	A6 66RFE	3.73	9,900	3,030	6,868	3,998	2,870	5,500	6,000	19,800	12,460
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,030	6,868	3,998	2,870	5,500	6,000	22,800	15,460
6.7L CUMMINS DIESEL	A6 68RFE	3.42	9,900	2,100	7,804	4,851	2,953	5,750	6,000	25,300	15,690
6.7L CUMMINS DIESEL	M6 MT-G56	3.42	9,900	2,030	7,875	4,915	2,960	5,750	6,000	24,300	15,140
CREW CAB, SHORT BOX, 4X4, POWER WAGON											
6.4L V8 HEMI	A6 66RFE	4.10	8,565	1,560	7,000	4,139	2,861	4,750	6,200	17,525	10,050

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.

Passenger Weight = 300 lb

Options Weight = 100 lb

Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for 5th Wheel or Gooseneck hitch.

Trailing Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.

Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailering equipment and tongue weight.

Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.

8. The maximum tongue weight for Class V (receiver hitch) is limited to 1,800 lb.

9. Maximum Capability

2018 Ram 2500 Trailer Towing Chart – SAE J2807 Compliant											
Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
MEGA CA,B SHORT BOX, 4X2											
5.7 GAS HEMI	A6 66RFE	3.73	9,000	2,210	6,787	3,754	3,033	5,000	6,200	18,300	11,040
5.7 GAS HEMI	A6 66RFE	4.10	9,000	2,210	6,787	3,754	3,033	5,000	6,200	20,300	13,040
6.4 GAS HEMI	A6 66RFE	3.73	10,000	3,180	6,818	3,795	3,023	5,500	6,500	19,800	12,510
6.4 GAS HEMI	A6 66RFE	4.10	10,000	3,180	6,818	3,795	3,023	5,500	6,500	22,800	15,510
6.7 DIESEL CUMMINS	M6 MT-G56	3.42	10,000	2,270	7,726	4,695	3,031	5,500	6,500	24,300	16,100
6.7 DIESEL CUMMINS	A6 68RFE	3.42	10,000	2,340	7,658	4,634	3,024	5,500	6,500	25,300	17,170
MEGA CAB, SHORT BOX, 4X2, CANADA ONLY											
6.4 GAS HEMI	A6 66RFE	3.73	9,900	3,090	6,807	3,777	3,030	5,500	6,500	19,800	12,520
6.4 GAS HEMI	A6 66RFE	4.10	9,900	3,090	6,807	3,777	3,030	5,500	6,500	22,800	15,520
6.7 DIESEL CUMMINS	M6 MT-G56	3.42	9,900	2,170	7,726	4,695	3,031	5,500	6,500	24,300	16,100
6.7 DIESEL CUMMINS	A6 68RFE	3.42	9,900	2,240	7,658	4,634	3,024	5,500	6,500	25,300	17,170
MEGA CA,B SHORT BOX, 4X4											
5.7 GAS HEMI	A6 66RFE	3.73	9,000	1,960	7,042	4,008	3,034	5,250	6,200	18,300	10,780
5.7 GAS HEMI	A6 66RFE	4.10	9,000	1,960	7,042	4,008	3,034	5,250	6,200	20,300	12,780
6.4 GAS HEMI	A6 66RFE	3.73	10,000	2,910	7,090	4,056	3,035	5,500	6,500	19,800	12,240
6.4 GAS HEMI	A6 66RFE	4.10	10,000	2,910	7,090	4,056	3,035	5,500	6,500	22,800	15,240
6.7 DIESEL CUMMINS	M6 MT-G56	3.42	10,000	1,950	8,050	4,954	3,096	6,000	6,500	24,300	14,750
6.7 DIESEL CUMMINS	A6 68RFE	3.42	10,000	2,020	7,982	4,892	3,090	6,000	6,500	25,300	15,430
MEGA CAB, SHORT BOX, 4X4, CANADA ONLY											
6.4 GAS HEMI	A6 66RFE	3.73	9,900	2,810	7,090	4,056	3,035	5,500	6,500	19,800	12,240
6.4 GAS HEMI	A6 66RFE	4.10	9,900	2,810	7,090	4,056	3,035	5,500	6,500	22,800	15,240
6.7 DIESEL CUMMINS	M6 MT-G56	3.42	9,900	1,850	8,050	4,954	3,096	6,000	6,500	24,300	13,750
6.7 DIESEL CUMMINS	A6 68RFE	3.42	9,900	1,920	7,982	4,892	3,090	6,000	6,500	25,300	14,430

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.

Passenger Weight = 300 lb

Options Weight = 100 lb

Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for 5th Wheel or Gooseneck hitch.

Trailing Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.

Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailering equipment and tongue weight.

Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.

8. The maximum tongue weight for Class V (receiver hitch) is limited to 1,800 lb.

9. Maximum Capability

2018 Ram 2500 Trailer Towing Chart – SAE J2807 Compliant												
Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating	
					Total	Front	Rear	Front	Rear			
CREW CAB, SHORT BOX, 4X2 - BOX OFF												
6.4L V8 HEMI	A6 66RFE	3.73	10,000	3,990	6,011	3,679	2,332	5,500	6,500	19,800	12,750	
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,990	6,011	3,679	2,332	5,500	6,500	22,800	15,750	
CREW CAB, SHORT BOX, 4X2 - BOX OFF CANADA ONLY												
6.4L V8 HEMI	A6 66RFE	3.73	9,900	3,890	6,011	3,679	2,332	5,500	6,500	19,800	12,750	
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,890	6,011	3,679	2,332	5,500	6,500	22,800	15,750	
CREW CAB, LONG BOX, 4X2 - BOX OFF												
6.4L V8 HEMI	A6 66RFE	3.73	10,000	3,950	6,049	3,727	2,322	5,500	6,500	19,800	12,640	
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,950	6,049	3,727	2,322	5,500	6,500	22,800	15,640	
CREW CAB, LONG BOX, 4X2 - BOX OFF CANADA ONLY												
6.4L V8 HEMI	A6 66RFE	3.73	9,900	3,850	6,049	3,727	2,322	5,500	6,500	19,800	12,640	
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,850	6,049	3,727	2,322	5,500	6,500	22,800	15,640	
CREW CAB, SHORT BOX, 4X4 - BOX OFF												
6.4L V8 HEMI	A6 66RFE	3.73	10,000	3,690	6,311	3,947	2,363	5,500	6,500	19,800	12,450	
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,690	6,311	3,947	2,363	5,500	6,500	22,800	15,450	
CREW CAB, SHORT BOX, 4X4 - BOX OFF CANADA ONLY												
6.4L V8 HEMI	A6 66RFE	3.73	9,900	3,590	6,311	3,947	2,363	5,500	6,500	19,800	12,450	
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,590	6,311	3,947	2,363	5,500	6,500	22,800	15,450	
CREW CAB, LONG BOX, 4X4 - BOX OFF												
6.4L V8 HEMI	A6 66RFE	3.73	10,000	3,590	6,408	4,020	2,389	5,500	6,500	19,800	12,280	
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,590	6,408	4,020	2,389	5,500	6,500	22,800	15,280	
CREW CAB, LONG BOX, 4X4 - BOX OFF CANADA ONLY												
6.4L V8 HEMI	A6 66RFE	3.73	9,900	3,470	6,425	3,989	2,436	5,500	6,500	19,800	12,260	
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,470	6,425	3,989	2,436	5,500	6,500	22,800	15,260	

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailering Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb
 Options Weight = 100 lb
 Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for 5th Wheel or Gooseneck hitch.
 Trailering Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.
 Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailering equipment and tongue weight.
 Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.
8. The maximum tongue weight for Class V (receiver hitch) is limited to 1,800 lb.
9. Maximum Capability

2018 Ram 2500 Trailer Towing Chart – SAE J2807 Compliant											
Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
REG CAB, LONG BOX, 4X2 - BOX OFF											
6.4L V8 HEMI	A6 66RFE	3.73	10,000	4,490	5,510	3,399	2,111	5,500	6,500	19,800	13,160
6.4L V8 HEMI	A6 66RFE	4.10	10,000	4,490	5,510	3,399	2,111	5,500	6,500	22,800	16,160
REG CAB, LONG BOX, 4X2 - BOX OFF, CANADA ONLY											
6.4L V8 HEMI	A6 66RFE	3.73	9,900	4,390	5,510	3,399	2,111	5,500	6,500	19,800	13,160
6.4L V8 HEMI	A6 66RFE	4.10	9,900	4,390	5,510	3,399	2,111	5,500	6,500	22,800	16,160
REG CAB, LONG BOX, 4X4 - BOX OFF											
6.4L V8 HEMI	A6 66RFE	3.73	10,000	4,100	5,901	3,763	2,139	5,500	6,500	19,800	12,770
6.4L V8 HEMI	A6 66RFE	4.10	10,000	4,100	5,901	3,763	2,139	5,500	6,500	22,800	15,770
REG CAB, LONG BOX, 4X4 - BOX OFF, CANADA ONLY											
6.4L V8 HEMI	A6 66RFE	3.73	9,900	4,000	5,898	3,689	2,210	5,500	6,500	19,800	12,780
6.4L V8 HEMI	A6 66RFE	4.10	9,900	4,000	5,898	3,689	2,210	5,500	6,500	22,800	15,780

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailering Weight are calculated as specified in SAE J2807.

Passenger Weight = 300 lb

Options Weight = 100 lb

Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for 5th Wheel or Gooseneck hitch.

Trailering Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.

Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailering equipment and tongue weight.

Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.

8. The maximum tongue weight for Class V (receiver hitch) is limited to 1,800 lb.

9. Maximum Capability