Official J1

2018 RAM - Promaster City - Trailer Towing Chart - SAE J2807 compliant												
Engine	Transmission	Mkt	Axle Ratio	GVWR	Payload [1]	Base Weight			GAWR		GCWR[2]	Max. Trailer Weight Rating[3]
						Total	Front	Rear	Front	Rear		
RAM Promaster City												
2.4L I4 GASOLINE MULTIAIR ENGINE	9-SPD AUTO 948TE - DFH	USA	3.73	5,395	1,885	3,510	2,212	1,298	2,690	2,866	5,900	2,000
2.4L I4 GASOLINE MULTIAIR ENGINE	9-SPD AUTO 948TE - DFH	CAN	3.73	5,395	1,901	3,494	2,208	1,286	2,690	2,866	5,900	2,000

1 . Payload and Max Trailer weights are ESTIMATED values.

2 . All values are shown in pounds unless otherwise stated

3 . (1) Payload. (Payload = GVWR - Base Weight)

4 . (2) GCWR is a defined value from Vehicle Engineering in lbs (max GCWR = 5,900 lbs)

5 . (3) Max Trailer weight is limited to 2,000 lbs.

6 . Payload and Maximum Trailer weight are mutually exclusive.

7 . Trailer Weight Rating and Tow Vehicle Trailering Weight are calculated as specified in SAE J2807.

Driver and passenger Weight = 300 lb.

Trailering Equipment Weight: 57.0 lb for Convencional Hitch.

8 . The recommended tongue weight is 10% of trailer weight.

9 . Hitch rating, GAWRs, and GCWR should never be exceeded.