


### 2020 Ram 3500 Sub 10K (DF) Chassis Cab Trailer Towing Chart

	Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		VECI Label		UVW	Max Upfit Weight	GCWR	Max Trailer
						Total	Front	Rear	Front	Rear	MCVW	Frontal Area (ft <sup>2</sup> )				
<b>US Market</b>	<b>REGULAR CAB - CA 60" - 4X2 - SRW</b>															
	6.4L V8 HEMI	8HP75	4.10	10,000	4,230	5,770	3,526	2,244	5,500	6,800	8,500	58	8,000	2,230	24,000	18,080
	<b>REGULAR CAB - CA 60" - 4X4 - SRW</b>															
	6.4L V8 HEMI	8HP75	4.10	10,000	3,990	6,013	3,732	2,281	5,500	6,800	8,500	58	8,000	1,987	24,000	17,840
	<b>CREW CAB - CA 60" - 4X2 - SRW</b>															
	6.4L V8 HEMI	8HP75	4.10	10,000	3,790	6,210	3,692	2,518	5,500	6,800	8,500	58	8,000	1,790	24,000	17,640
<b>CREW CAB - CA 60" - 4X4 - SRW</b>																
6.4L V8 HEMI	8HP75	4.10	10,000	3,470	6,529	3,950	2,579	5,500	6,800	8,500	58	8,000	1,471	24,000	17,320	
<b>Canadian Market</b>	<b>REGULAR CAB - CA 60" - 4X2 - SRW</b>															
	6.4L V8 HEMI	8HP75	4.10	9,900	4,130	5,770	3,526	2,244	5,500	6,800	8,500	58	8,000	2,230	24,000	17,050
	<b>REGULAR CAB - CA 60" - 4X4 - SRW</b>															
	6.4L V8 HEMI	8HP75	4.10	9,900	3,890	6,013	3,732	2,281	5,500	6,800	8,500	58	8,000	1,987	24,000	17,050
	<b>CREW CAB - CA 60" - 4X2 - SRW</b>															
	6.4L V8 HEMI	8HP75	4.10	9,900	3,690	6,210	3,692	2,518	5,500	6,800	8,500	58	8,000	1,790	24,000	17,050
<b>CREW CAB - CA 60" - 4X4 - SRW</b>																
6.4L V8 HEMI	8HP75	4.10	9,900	3,370	6,529	3,950	2,579	5,500	6,800	8,500	58	8,000	1,471	24,000	17,050	
<b>Notes</b>	Payload and Max Trailer Weights are ESTIMATED values <span style="background-color: yellow; border: 1px solid black; padding: 0 5px;"> </span> Indicates Max Payload/Trailer option (NOTE 4x2 or 4x4 AND Market) All values are shown in pounds unless otherwise stated Payload and Max Trailer Weight values are rounded to the nearest 10 lbs Payload = GVWR - Base Weight GAWRs, GVWRs, and GCWRs should never be exceeded Recommended tongue weight determined by class hitch receiver and hardware limits of upfit Upfit or Aftermarket equipment weight not included in Base Weight MCVW: Maximum Completed Vehicle Weight, includes Total Base Weight + permanently attached Upfit Weight Frontal Area: Maximum allowable Frontal Area, in Ft <sup>2</sup> , that the vehicle can project. For details on calculations please refer to Ram Body Builders Guide. If VECI Label & Max Upfit Weight n/a: Vehicle is not restricted to MCVW, Frontal Area, or Maximum Upfit Weight limits, however GVWR/GAWR/GCWR cannot be exceeded.															



	Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
						Total	Front	Rear	Front	Rear		
4x2	<b>REGULAR CAB - CA 60" - 4X2 - DRW</b>											
	6.4L V8 HEMI	A6 AS66RC	4.44	15,000	8,190	6,808	3,770	3,038	6,000	12,000	26,000	19,040
	6.4L V8 HEMI	A6 AS66RC	4.89	15,000	8,190	6,808	3,770	3,038	6,000	12,000	28,500	21,540
	6.4L V8 HEMI	A6 AS66RC	4.44	16,000	9,190	6,808	3,770	3,038	6,000	12,000	26,000	19,040
	6.4L V8 HEMI	A6 AS66RC	4.89	16,000	9,190	6,808	3,770	3,038	6,000	12,000	28,500	21,540
	6.4L V8 HEMI	A6 AS66RC	4.44	16,500	9,690	6,808	3,770	3,038	6,000	12,000	26,000	19,040
	6.4L V8 HEMI	A6 AS66RC	4.89	16,500	9,690	6,808	3,770	3,038	6,000	12,000	28,500	21,540
	<b>REGULAR CAB - CA 84" - 4X2 - DRW</b>											
	6.4L V8 HEMI	A6 AS66RC	4.44	15,000	8,030	6,973	3,880	3,093	6,000	12,000	26,000	18,880
	6.4L V8 HEMI	A6 AS66RC	4.89	15,000	8,030	6,973	3,880	3,093	6,000	12,000	28,500	21,380
	6.4L V8 HEMI	A6 AS66RC	4.44	16,000	9,030	6,973	3,880	3,093	6,000	12,000	26,000	18,880
	6.4L V8 HEMI	A6 AS66RC	4.89	16,000	9,030	6,973	3,880	3,093	6,000	12,000	28,500	21,380
	6.4L V8 HEMI	A6 AS66RC	4.44	16,500	9,530	6,973	3,880	3,093	6,000	12,000	26,000	18,880
	6.4L V8 HEMI	A6 AS66RC	4.89	16,500	9,530	6,973	3,880	3,093	6,000	12,000	28,500	21,380
	<b>REGULAR CAB - CA 108" - 4X2 - DRW</b>											
	6.4L V8 HEMI	A6 AS66RC	4.44	15,000	7,880	7,121	3,954	3,167	6,500	12,000	26,000	18,730
	6.4L V8 HEMI	A6 AS66RC	4.89	15,000	7,880	7,121	3,954	3,167	6,500	12,000	28,500	21,230
	6.4L V8 HEMI	A6 AS66RC	4.44	16,000	8,880	7,121	3,954	3,167	6,500	12,000	26,000	18,730
	6.4L V8 HEMI	A6 AS66RC	4.89	16,000	8,880	7,121	3,954	3,167	6,500	12,000	28,500	21,230
	6.4L V8 HEMI	A6 AS66RC	4.44	16,500	9,380	7,121	3,954	3,167	6,500	12,000	26,000	18,730
	6.4L V8 HEMI	A6 AS66RC	4.89	16,500	9,380	7,121	3,954	3,167	6,500	12,000	28,500	21,230

Notes	Payload and Max Trailer Weights are ESTIMATED values All values are shown in pounds unless otherwise stated Payload and Max Trailer Weight values are rounded to the nearest 10 lbs Payload = GVWR - Base Weight GAWRs, GVWRs, and GCWRs should never be exceeded Recommended tongue weight determined by class hitch receiver and hardware limits of upfit Upfit or Aftermarket equipment weight not included in Base Weight	 Indicates Max Payload/Trailer option (NOTE 4x2 or 4x4)
-------	---	--

**2020 RAM 4500 (DP) BASE WEIGHT GCW AND TRAILER TOW**



	Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
						Total	Front	Rear	Front	Rear		
4x2	<b>REGULAR CAB - CA 120" - 4X2 - DRW</b>											
	6.4L V8 HEMI	A6 AS66RC	4.44	15,000	7,740	7,261	4,024	3,237	6,500	12,000	26,000	18,590
	6.4L V8 HEMI	A6 AS66RC	4.89	15,000	7,740	7,261	4,024	3,237	6,500	12,000	28,500	21,090
	6.4L V8 HEMI	A6 AS66RC	4.44	16,000	8,740	7,261	4,024	3,237	6,500	12,000	26,000	18,590
	6.4L V8 HEMI	A6 AS66RC	4.89	16,000	8,740	7,261	4,024	3,237	6,500	12,000	28,500	21,090
	6.4L V8 HEMI	A6 AS66RC	4.44	16,500	9,240	7,261	4,024	3,237	6,500	12,000	26,000	18,590
	6.4L V8 HEMI	A6 AS66RC	4.89	16,500	9,240	7,261	4,024	3,237	6,500	12,000	28,500	21,090
	<b>CREW CAB - CA 60" - 4X2 - DRW</b>											
	6.4L V8 HEMI	A6 AS66RC	4.44	15,000	7,610	7,386	4,032	3,354	6,000	12,000	26,000	18,460
	6.4L V8 HEMI	A6 AS66RC	4.89	15,000	7,610	7,386	4,032	3,354	6,000	12,000	28,500	20,960
	6.4L V8 HEMI	A6 AS66RC	4.44	16,000	8,610	7,386	4,032	3,354	6,000	12,000	26,000	18,460
	6.4L V8 HEMI	A6 AS66RC	4.89	16,000	8,610	7,386	4,032	3,354	6,000	12,000	28,500	20,960
	6.4L V8 HEMI	A6 AS66RC	4.44	16,500	9,110	7,386	4,032	3,354	6,000	12,000	26,000	18,460
	6.4L V8 HEMI	A6 AS66RC	4.89	16,500	9,110	7,386	4,032	3,354	6,000	12,000	28,500	20,960
	<b>CREW CAB - CA 84" - 4X2 - DRW</b>											
	6.4L V8 HEMI	A6 AS66RC	4.44	15,000	7,470	7,526	4,216	3,310	6,000	12,000	26,000	18,320
	6.4L V8 HEMI	A6 AS66RC	4.89	15,000	7,470	7,526	4,216	3,310	6,000	12,000	28,500	20,820
	6.4L V8 HEMI	A6 AS66RC	4.44	16,000	8,470	7,526	4,216	3,310	6,000	12,000	26,000	18,320
6.4L V8 HEMI	A6 AS66RC	4.89	16,000	8,470	7,526	4,216	3,310	6,000	12,000	28,500	20,820	
6.4L V8 HEMI	A6 AS66RC	4.44	16,500	8,970	7,526	4,216	3,310	6,000	12,000	26,000	18,320	
6.4L V8 HEMI	A6 AS66RC	4.89	16,500	8,970	7,526	4,216	3,310	6,000	12,000	28,500	20,820	

Notes	Payload and Max Trailer Weights are ESTIMATED values <span style="background-color: yellow; border: 1px solid black; padding: 0 5px;"> </span> Indicates Max Payload/Trailer option (NOTE 4x2 or 4x4) All values are shown in pounds unless otherwise stated Payload and Max Trailer Weight values are rounded to the nearest 10 lbs Payload = GVWR - Base Weight GAWRs, GVWRs, and GCWRs should never be exceeded Recommended tongue weight determined by class hitch receiver and hardware limits of upfit Upfit or Aftermarket equipment weight not included in Base Weight
-------	--

**2020 RAM 4500 (DP) BASE WEIGHT GCW AND TRAILER TOW**



	Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
						Total	Front	Rear	Front	Rear		
4x4	<b>REGULAR CAB - CA 60" - 4X4 - DRW</b>											
	6.4L V8 HEMI	A6 AS66RC	4.44	15,000	7,800	7,197	4,037	3,160	6,000	12,000	26,000	18,650
	6.4L V8 HEMI	A6 AS66RC	4.89	15,000	7,800	7,197	4,037	3,160	6,000	12,000	28,500	21,150
	6.4L V8 HEMI	A6 AS66RC	4.44	16,000	8,800	7,197	4,037	3,160	6,000	12,000	26,000	18,650
	6.4L V8 HEMI	A6 AS66RC	4.89	16,000	8,800	7,197	4,037	3,160	6,000	12,000	28,500	21,150
	6.4L V8 HEMI	A6 AS66RC	4.44	16,500	9,300	7,197	4,037	3,160	6,000	12,000	26,000	18,650
	6.4L V8 HEMI	A6 AS66RC	4.89	16,500	9,300	7,197	4,037	3,160	6,000	12,000	28,500	21,150
	<b>REGULAR CAB - CA 84" - 4X4 - DRW</b>											
	6.4L V8 HEMI	A6 AS66RC	4.44	15,000	7,650	7,349	4,208	3,141	6,000	12,000	26,000	18,500
	6.4L V8 HEMI	A6 AS66RC	4.89	15,000	7,650	7,349	4,208	3,141	6,000	12,000	28,500	21,000
	6.4L V8 HEMI	A6 AS66RC	4.44	16,000	8,650	7,349	4,208	3,141	6,000	12,000	26,000	18,500
	6.4L V8 HEMI	A6 AS66RC	4.89	16,000	8,650	7,349	4,208	3,141	6,000	12,000	28,500	21,000
	6.4L V8 HEMI	A6 AS66RC	4.44	16,500	9,150	7,349	4,208	3,141	6,000	12,000	26,000	18,500
	6.4L V8 HEMI	A6 AS66RC	4.89	16,500	9,150	7,349	4,208	3,141	6,000	12,000	28,500	21,000
	<b>REGULAR CAB - CA 108" - 4X4 - DRW</b>											
	6.4L V8 HEMI	A6 AS66RC	4.44	15,000	7,530	7,467	3,953	3,514	6,500	12,000	26,000	18,380
	6.4L V8 HEMI	A6 AS66RC	4.89	15,000	7,530	7,467	3,953	3,514	6,500	12,000	28,500	20,880
	6.4L V8 HEMI	A6 AS66RC	4.44	16,000	8,530	7,467	3,953	3,514	6,500	12,000	26,000	18,380
	6.4L V8 HEMI	A6 AS66RC	4.89	16,000	8,530	7,467	3,953	3,514	6,500	12,000	28,500	20,880
	6.4L V8 HEMI	A6 AS66RC	4.44	16,500	9,030	7,467	3,953	3,514	6,500	12,000	26,000	18,380
	6.4L V8 HEMI	A6 AS66RC	4.89	16,500	9,030	7,467	3,953	3,514	6,500	12,000	28,500	20,880

Notes	Payload and Max Trailer Weights are ESTIMATED values <span style="background-color: yellow; border: 1px solid black; display: inline-block; width: 20px; height: 10px; vertical-align: middle;"></span> Indicates Max Payload/Trailer option (NOTE 4x2 or 4x4) All values are shown in pounds unless otherwise stated Payload and Max Trailer Weight values are rounded to the nearest 10 lbs Payload = GVWR - Base Weight GAWRs, GVWRs, and GCWRs should never be exceeded Recommended tongue weight determined by class hitch receiver and hardware limits of upfit Upfit or Aftermarket equipment weight not included in Base Weight
-------	---

**2020 RAM 4500 (DP) BASE WEIGHT GCW AND TRAILER TOW**




	Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
						Total	Front	Rear	Front	Rear		
4x4	<b>REGULAR CAB - CA 120" - 4X4 - DRW</b>											
	6.4L V8 HEMI	A6 AS66RC	4.44	15,000	7,470	7,528	3,984	3,544	6,500	12,000	26,000	18,320
	6.4L V8 HEMI	A6 AS66RC	4.89	15,000	7,470	7,528	3,984	3,544	6,500	12,000	28,500	20,820
	6.4L V8 HEMI	A6 AS66RC	4.44	16,000	8,470	7,528	3,984	3,544	6,500	12,000	26,000	18,320
	6.4L V8 HEMI	A6 AS66RC	4.89	16,000	8,470	7,528	3,984	3,544	6,500	12,000	28,500	20,820
	6.4L V8 HEMI	A6 AS66RC	4.44	16,500	8,970	7,528	3,984	3,544	6,500	12,000	26,000	18,320
	6.4L V8 HEMI	A6 AS66RC	4.89	16,500	8,970	7,528	3,984	3,544	6,500	12,000	28,500	20,820
	<b>CREW CAB - CA 60" - 4X4 - DRW</b>											
	6.4L V8 HEMI	A6 AS66RC	4.44	15,000	7,260	7,739	4,340	3,399	6,000	12,000	26,000	18,110
	6.4L V8 HEMI	A6 AS66RC	4.89	15,000	7,260	7,739	4,340	3,399	6,000	12,000	28,500	20,610
	6.4L V8 HEMI	A6 AS66RC	4.44	16,000	8,260	7,739	4,340	3,399	6,000	12,000	26,000	18,110
	6.4L V8 HEMI	A6 AS66RC	4.89	16,000	8,260	7,739	4,340	3,399	6,000	12,000	28,500	20,610
	6.4L V8 HEMI	A6 AS66RC	4.44	16,500	8,760	7,739	4,340	3,399	6,000	12,000	26,000	18,110
	6.4L V8 HEMI	A6 AS66RC	4.89	16,500	8,760	7,739	4,340	3,399	6,000	12,000	28,500	20,610
	<b>CREW CAB - CA 84" - 4X4 - DRW</b>											
	6.4L V8 HEMI	A6 AS66RC	4.44	15,000	7,170	7,830	4,498	3,332	6,000	12,000	26,000	18,020
	6.4L V8 HEMI	A6 AS66RC	4.89	15,000	7,170	7,830	4,498	3,332	6,000	12,000	28,500	20,520
	6.4L V8 HEMI	A6 AS66RC	4.44	16,000	8,170	7,830	4,498	3,332	6,000	12,000	26,000	18,020
	6.4L V8 HEMI	A6 AS66RC	4.89	16,000	8,170	7,830	4,498	3,332	6,000	12,000	28,500	20,520
	6.4L V8 HEMI	A6 AS66RC	4.44	16,500	8,670	7,830	4,498	3,332	6,000	12,000	26,000	18,020
	6.4L V8 HEMI	A6 AS66RC	4.89	16,500	8,670	7,830	4,498	3,332	6,000	12,000	28,500	20,520

Notes	Payload and Max Trailer Weights are ESTIMATED values <span style="background-color: yellow; border: 1px solid black; padding: 2px;"> </span> Indicates Max Payload/Trailer option (NOTE 4x2 or 4x4) All values are shown in pounds unless otherwise stated Payload and Max Trailer Weight values are rounded to the nearest 10 lbs Payload = GVWR - Base Weight GAWRs, GVWRs, and GCWRs should never be exceeded Recommended tongue weight determined by class hitch receiver and hardware limits of upfit Upfit or Aftermarket equipment weight not included in Base Weight
-------	--

**2020 RAM 4500 (DP) BASE WEIGHT GCW AND TRAILER TOW**




	Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
						Total	Front	Rear	Front	Rear		
4x2	<b>REGULAR CAB - CA 60" - 4X2 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	15,000	7,420	7,580	4,408	3,172	7000/7250	12,000	32,000	24,270
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	15,000	7,420	7,580	4,408	3,172	7000/7250	12,000	37,500	29,770
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,000	8,420	7,580	4,408	3,172	7000/7250	12,000	32,000	24,270
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,000	8,420	7,580	4,408	3,172	7000/7250	12,000	37,500	29,770
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,500	8,920	7,580	4,408	3,172	7000/7250	12,000	32,000	24,270
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,500	8,920	7,580	4,408	3,172	7000/7250	12,000	37,500	29,770
	<b>REGULAR CAB - CA 84" - 4X2 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	15,000	7,190	7,814	4,578	3,236	7000/7250	12,000	32,000	24,040
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	15,000	7,190	7,814	4,578	3,236	7000/7250	12,000	37,500	29,540
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,000	8,190	7,814	4,578	3,236	7000/7250	12,000	32,000	24,040
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,000	8,190	7,814	4,578	3,236	7000/7250	12,000	37,500	29,540
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,500	8,690	7,814	4,578	3,236	7000/7250	12,000	32,000	24,040
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,500	8,690	7,814	4,578	3,236	7000/7250	12,000	37,500	29,540
	<b>REGULAR CAB - CA 108" - 4X2 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	15,000	7,100	7,899	4,619	3,280	7000/7250	12,000	32,000	23,950
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	15,000	7,100	7,899	4,619	3,280	7000/7250	12,000	37,500	29,450
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,000	8,100	7,899	4,619	3,280	7000/7250	12,000	32,000	23,950
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,000	8,100	7,899	4,619	3,280	7000/7250	12,000	37,500	29,450
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,500	8,600	7,899	4,619	3,280	7000/7250	12,000	32,000	23,950
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,500	8,600	7,899	4,619	3,280	7000/7250	12,000	37,500	29,450

Notes	Payload and Max Trailer Weights are ESTIMATED values All values are shown in pounds unless otherwise stated Payload and Max Trailer Weight values are rounded to the nearest 10 lbs Payload = GVWR - Base Weight GAWRs, GVWRs, and GCWRs should never be exceeded Recommended tongue weight determined by class hitch receiver and hardware limits of upfit Upfit or Aftermarket equipment weight not included in Base Weight	 Indicates Max Payload/Trailer option (NOTE 4x2 or 4x4)
-------	---	--

**2020 RAM 4500 (DP) BASE WEIGHT GCW AND TRAILER TOW**




	Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
						Total	Front	Rear	Front	Rear		
4x2	<b>REGULAR CAB - CA 120" - 4X2 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	15,000	7,020	7,979	4,659	3,320	7000/7250	12,000	32,000	23,870
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	15,000	7,020	7,979	4,659	3,320	7000/7250	12,000	37,500	29,370
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,000	8,020	7,979	4,659	3,320	7000/7250	12,000	32,000	23,870
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,000	8,020	7,979	4,659	3,320	7000/7250	12,000	37,500	29,370
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,500	8,520	7,979	4,659	3,320	7000/7250	12,000	32,000	23,870
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,500	8,520	7,979	4,659	3,320	7000/7250	12,000	37,500	29,370
	<b>CREW CAB - CA 60" - 4X2 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	15,000	6,770	8,227	4,750	3,477	7000/7250	12,000	32,000	23,620
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	15,000	6,770	8,227	4,750	3,477	7000/7250	12,000	37,500	29,120
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,000	7,770	8,227	4,750	3,477	7000/7250	12,000	32,000	23,620
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,000	7,770	8,227	4,750	3,477	7000/7250	12,000	37,500	29,120
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,500	8,270	8,227	4,750	3,477	7000/7250	12,000	32,000	23,620
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,500	8,270	8,227	4,750	3,477	7000/7250	12,000	37,500	29,120
	<b>CREW CAB - CA 84" - 4X2 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	15,000	6,630	8,367	4,934	3,433	7000/7250	12,000	32,000	23,480
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	15,000	6,630	8,367	4,934	3,433	7000/7250	12,000	37,500	28,980
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,000	7,630	8,367	4,934	3,433	7000/7250	12,000	32,000	23,480
6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,000	7,630	8,367	4,934	3,433	7000/7250	12,000	37,500	28,980	
6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,500	8,130	8,367	4,934	3,433	7000/7250	12,000	32,000	23,480	
6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,500	8,130	8,367	4,934	3,433	7000/7250	12,000	37,500	28,980	

Notes	Payload and Max Trailer Weights are ESTIMATED values All values are shown in pounds unless otherwise stated Payload and Max Trailer Weight values are rounded to the nearest 10 lbs Payload = GVWR - Base Weight GAWRs, GVWRs, and GCWRs should never be exceeded Recommended tongue weight determined by class hitch receiver and hardware limits of upfit Upfit or Aftermarket equipment weight not included in Base Weight	 Indicates Max Payload/Trailer option (NOTE 4x2 or 4x4)
-------	---	--

**2020 RAM 4500 (DP) BASE WEIGHT GCW AND TRAILER TOW**



	Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
						Total	Front	Rear	Front	Rear		
4x4	<b>REGULAR CAB - CA 60" - 4X4 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	15,000	7,020	7,980	4,715	3,265	7000/7250	12,000	32,000	23,870
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	15,000	7,020	7,980	4,715	3,265	7000/7250	12,000	37,500	29,370
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,000	8,020	7,980	4,715	3,265	7000/7250	12,000	32,000	23,870
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,000	8,020	7,980	4,715	3,265	7000/7250	12,000	37,500	29,370
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,500	8,520	7,980	4,715	3,265	7000/7250	12,000	32,000	23,870
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,500	8,520	7,980	4,715	3,265	7000/7250	12,000	37,500	29,370
	<b>REGULAR CAB - CA 84" - 4X4 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	15,000	6,810	8,190	4,926	3,264	7000/7250	12,000	32,000	23,660
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	15,000	6,810	8,190	4,926	3,264	7000/7250	12,000	37,500	29,160
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,000	7,810	8,190	4,926	3,264	7000/7250	12,000	32,000	23,660
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,000	7,810	8,190	4,926	3,264	7000/7250	12,000	37,500	29,160
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,500	8,310	8,190	4,926	3,264	7000/7250	12,000	32,000	23,660
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,500	8,310	8,190	4,926	3,264	7000/7250	12,000	37,500	29,160
	<b>REGULAR CAB - CA 108" - 4X4 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	15,000	6,690	8,310	4,672	3,638	7000/7250	12,000	32,000	23,540
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	15,000	6,690	8,310	4,672	3,638	7000/7250	12,000	37,500	29,040
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,000	7,690	8,310	4,672	3,638	7000/7250	12,000	32,000	23,540
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,000	7,690	8,310	4,672	3,638	7000/7250	12,000	37,500	29,040
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,500	8,190	8,310	4,672	3,638	7000/7250	12,000	32,000	23,540
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,500	8,190	8,310	4,672	3,638	7000/7250	12,000	37,500	29,040


Notes	Payload and Max Trailer Weights are ESTIMATED values All values are shown in pounds unless otherwise stated Payload and Max Trailer Weight values are rounded to the nearest 10 lbs Payload = GVWR - Base Weight GAWRs, GVWRs, and GCWRs should never be exceeded Recommended tongue weight determined by class hitch receiver and hardware limits of upfit Upfit or Aftermarket equipment weight not included in Base Weight	 Indicates Max Payload/Trailer option (NOTE 4x2 or 4x4)
-------	---	--

**2020 RAM 4500 (DP) BASE WEIGHT GCW AND TRAILER TOW**





	Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
						Total	Front	Rear	Front	Rear		
4x4	<b>REGULAR CAB - CA 120" - 4X4 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	15,000	6,630	8,370	4,702	3,668	7000/7250	12,000	32,000	23,480
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	15,000	6,630	8,370	4,702	3,668	7000/7250	12,000	37,500	28,980
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,000	7,630	8,370	4,702	3,668	7000/7250	12,000	32,000	23,480
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,000	7,630	8,370	4,702	3,668	7000/7250	12,000	37,500	28,980
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,500	8,130	8,370	4,702	3,668	7000/7250	12,000	32,000	23,480
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,500	8,130	8,370	4,702	3,668	7000/7250	12,000	37,500	28,980
	<b>CREW CAB - CA 60" - 4X4 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	15,000	6,420	8,580	5,078	3,502	7000/7250	12,000	32,000	23,270
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	15,000	6,420	8,580	5,078	3,502	7000/7250	12,000	37,500	28,770
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,000	7,420	8,580	5,078	3,502	7000/7250	12,000	32,000	23,270
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,000	7,420	8,580	5,078	3,502	7000/7250	12,000	37,500	28,770
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,500	7,920	8,580	5,078	3,502	7000/7250	12,000	32,000	23,270
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,500	7,920	8,580	5,078	3,502	7000/7250	12,000	37,500	28,770
	<b>CREW CAB - CA 84" - 4X4 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	15,000	6,330	8,671	5,236	3,435	7000/7250	12,000	32,000	23,180
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	15,000	6,330	8,671	5,236	3,435	7000/7250	12,000	37,500	28,680
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,000	7,330	8,671	5,236	3,435	7000/7250	12,000	32,000	23,180
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,000	7,330	8,671	5,236	3,435	7000/7250	12,000	37,500	28,680
	6.7L CUMMINS DIESEL	A6 AS69RC	4.10	16,500	7,830	8,671	5,236	3,435	7000/7250	12,000	32,000	23,180
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	16,500	7,830	8,671	5,236	3,435	7000/7250	12,000	37,500	28,680

Notes	Payload and Max Trailer Weights are ESTIMATED values All values are shown in pounds unless otherwise stated Payload and Max Trailer Weight values are rounded to the nearest 10 lbs Payload = GVWR - Base Weight GAWRs, GVWRs, and GCWRs should never be exceeded Recommended tongue weight determined by class hitch receiver and hardware limits of upfit Upfit or Aftermarket equipment weight not included in Base Weight	 Indicates Max Payload/Trailer option (NOTE 4x2 or 4x4)
-------	---	--

**2020 RAM 4500 (DP) BASE WEIGHT GCW AND TRAILER TOW**



	Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
						Total	Front	Rear	Front	Rear		
4x2	<b>REGULAR CAB - CA 60" - 4X2 - DRW</b>											
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	11,140	6,862	3,750	3,112	6,000 / 6,500	13,500	26,000	18,990
	6.4L V8 HEMI	A6 AS66RC	4.89	19,000	12,140	6,862	3,750	3,112	6,000 / 6,500	13,500	28,500	21,490
	<b>REGULAR CAB - CA 84" - 4X2 - DRW</b>											
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	11,010	6,988	3,890	3,098	6,000 / 6,500	13,500	26,000	18,860
	6.4L V8 HEMI	A6 AS66RC	4.89	19,500	12,510	6,988	3,890	3,098	6,000 / 6,500	13,500	28,500	21,360
	<b>REGULAR CAB - CA 108" - 4X2 - DRW</b>											
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	10,840	7,160	4,031	3,129	6,500 / 7,000	13,500	26,000	18,690
	6.4L V8 HEMI	A6 AS66RC	4.89	19,500	12,340	7,160	4,031	3,129	6,500 / 7,000	13,500	28,500	21,190
	<b>REGULAR CAB - CA 120" - 4X2 - DRW</b>											
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	10,790	7,212	4,076	3,136	6,500 / 7,000	13,500	26,000	18,640
	6.4L V8 HEMI	A6 AS66RC	4.89	19,500	12,290	7,212	4,076	3,136	6,500 / 7,000	13,500	28,500	21,140
	<b>CREW CAB - CA 60" - 4X2 - DRW</b>											
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	10,630	7,369	4,033	3,336	6,000 / 7,000	13,500	26,000	18,480
	6.4L V8 HEMI	A6 AS66RC	4.89	19,000	11,630	7,369	4,033	3,336	6,000 / 7,000	13,500	28,500	20,980
	<b>CREW CAB - CA 84" - 4X2 - DRW</b>											
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	10,440	7,562	4,211	3,351	6,000 / 7,000	13,500	26,000	18,290
	6.4L V8 HEMI	A6 AS66RC	4.89	19,500	11,940	7,562	4,211	3,351	6,000 / 7,000	13,500	28,500	20,790

Notes	Payload and Max Trailer Weights are ESTIMATED values	Indicates Max Payload/Trailer option (NOTE 4x2 or 4x4)
	All values are shown in pounds unless otherwise stated	
	Payload and Max Trailer Weight values are rounded to the nearest 10 lbs	
	Payload = GVWR - Base Weight	
	GAWRs, GVWRs, and GCWRs should never be exceeded	
	Recommended tongue weight determined by class hitch receiver and hardware limits of upfit	
	Upfit or Aftermarket equipment weight not included in Base Weight	

**2020 RAM 5500 (DP) BASE WEIGHT GCW AND TRAILER TOW**




	Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer	
						Total	Front	Rear	Front	Rear			
4x4	<b>REGULAR CAB - CA 60" - 4X4 - DRW</b>												
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	10,770	7,234	4,049	3,185	6,000 / 6,500		13,500	26,000	18,620
	6.4L V8 HEMI	A6 AS66RC	4.89	19,000	11,770	7,234	4,049	3,185	6,000 / 6,500		13,500	28,500	21,120
	<b>REGULAR CAB - CA 84" - 4X4 - DRW</b>												
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	10,630	7,366	4,215	3,151	6,000 / 6,500		13,500	26,000	18,480
	6.4L V8 HEMI	A6 AS66RC	4.89	19,500	12,130	7,366	4,215	3,151	6,000 / 6,500		13,500	28,500	20,980
	<b>REGULAR CAB - CA 108" - 4X4 - DRW</b>												
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	10,490	7,510	4,349	3,161	6,500 / 7,000		13,500	26,000	18,340
	6.4L V8 HEMI	A6 AS66RC	4.89	19,500	11,990	7,510	4,349	3,161	6,500 / 7,000		13,500	28,500	20,840
	<b>REGULAR CAB - CA 120" - 4X4 - DRW</b>												
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	10,410	7,588	4,410	3,178	6,500 / 7,000		13,500	26,000	18,260
	6.4L V8 HEMI	A6 AS66RC	4.89	19,500	11,910	7,588	4,410	3,178	6,500 / 7,000		13,500	28,500	20,760
	<b>CREW CAB - CA 60" - 4X4 - DRW</b>												
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	10,250	7,750	4,364	3,386	6,000 / 7,000		13,500	26,000	18,100
	6.4L V8 HEMI	A6 AS66RC	4.89	19,000	11,250	7,750	4,364	3,386	6,000 / 7,000		13,500	28,500	20,600
	<b>CREW CAB - CA 84" - 4X4 - DRW</b>												
	6.4L V8 HEMI	A6 AS66RC	4.44	18,000	10,080	7,920	4,530	3,390	6,000 / 7,000		13,500	26,000	17,930
	6.4L V8 HEMI	A6 AS66RC	4.89	19,500	11,580	7,920	4,530	3,390	6,000 / 7,000		13,500	28,500	20,430

Notes	Payload and Max Trailer Weights are ESTIMATED values <span style="float: right;">■ Indicates Max Payload/Trailer option (NOTE 4x2 or 4x4)</span> All values are shown in pounds unless otherwise stated Payload and Max Trailer Weight values are rounded to the nearest 10 lbs Payload = GVWR - Base Weight GAWRs, GVWRs, and GCWRs should never be exceeded Recommended tongue weight determined by class hitch receiver and hardware limits of upfit Upfit or Aftermarket equipment weight not included in Base Weight
-------	---

**2020 RAM 5500 (DP) BASE WEIGHT GCW AND TRAILER TOW**



	Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
						Total	Front	Rear	Front	Rear		
4x2	<b>REGULAR CAB - CA 60" - 4X2 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	11,870	7,629	4,498	3,131	7,000 / 7,250	13,500	32,000	24,220
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	11,870	7,629	4,498	3,131	7,000 / 7,250	13,500	43,000	35,220
	<b>REGULAR CAB - CA 84" - 4X2 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	11,750	7,754	4,568	3,186	7,000 / 7,250	13,500	32,000	24,100
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	11,750	7,754	4,568	3,186	7,000 / 7,250	13,500	43,000	35,100
	<b>REGULAR CAB - CA 108" - 4X2 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	11,660	7,839	4,609	3,230	7,000 / 7,250	13,500	32,000	24,010
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	11,660	7,839	4,609	3,230	7,000 / 7,250	13,500	43,000	35,010
	<b>REGULAR CAB - CA 120" - 4X2 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	11,570	7,929	4,654	3,275	7,000 / 7,250	13,500	32,000	23,920
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	11,570	7,929	4,654	3,275	7,000 / 7,250	13,500	43,000	34,920
	<b>CREW CAB - CA 60" - 4X2 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	11,290	8,210	4,751	3,459	7,000 / 7,250	13,500	32,000	23,640
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	11,290	8,210	4,751	3,459	7,000 / 7,250	13,500	43,000	34,640
	<b>CREW CAB - CA 84" - 4X2 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	11,100	8,403	4,929	3,474	7,000 / 7,250	13,500	32,000	23,450
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	11,100	8,403	4,929	3,474	7,000 / 7,250	13,500	43,000	34,450

Notes	Payload and Max Trailer Weights are ESTIMATED values All values are shown in pounds unless otherwise stated Payload and Max Trailer Weight values are rounded to the nearest 10 lbs Payload = GVWR - Base Weight GAWRs, GVWRs, and GCWRs should never be exceeded Recommended tongue weight determined by class hitch receiver and hardware limits of upfit Upfit or Aftermarket equipment weight not included in Base Weight	 Indicates Max Payload/Trailer option (NOTE 4x2 or 4x4)
-------	---	--

**2020 RAM 5500 (DP) BASE WEIGHT GCW AND TRAILER TOW**



	Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
						Total	Front	Rear	Front	Rear		
4x4	<b>REGULAR CAB - CA 60" - 4X4 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	11,450	8,047	4,748	3,299	7,000 / 7,250	13,500	32,000	23,800
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	11,450	8,047	4,748	3,299	7,000 / 7,250	13,500	43,000	34,800
	<b>REGULAR CAB - CA 84" - 4X4 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	11,320	8,179	4,914	3,265	7,000 / 7,250	13,500	32,000	23,670
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	11,320	8,179	4,914	3,265	7,000 / 7,250	13,500	43,000	34,670
	<b>REGULAR CAB - CA 108" - 4X4 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	11,180	8,323	5,048	3,275	7,000 / 7,250	13,500	32,000	23,530
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	11,180	8,323	5,048	3,275	7,000 / 7,250	13,500	43,000	34,530
	<b>REGULAR CAB - CA 120" - 4X4 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	11,100	8,401	5,109	3,292	7,000 / 7,250	13,500	32,000	23,450
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	11,100	8,401	5,109	3,292	7,000 / 7,250	13,500	43,000	34,450
	<b>CREW CAB - CA 60" - 4X4 - DRW</b>											
	6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	10,940	8,563	5,063	3,500	7,000 / 7,250	13,500	32,000	23,290
	6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	10,940	8,563	5,063	3,500	7,000 / 7,250	13,500	43,000	34,290
	<b>CREW CAB - CA 84" - 4X4 - DRW</b>											
6.7L CUMMINS DIESEL	A6 AS69RC	4.44	19,500	10,770	8,733	5,229	3,504	7,000 / 7,250	13,500	32,000	23,120	
6.7L CUMMINS DIESEL	A6 AS69RC	4.89	19,500	10,770	8,733	5,229	3,504	7,000 / 7,250	13,500	43,000	34,120	

Notes	Payload and Max Trailer Weights are ESTIMATED values <span style="background-color: yellow;">    </span> Indicates Max Payload/Trailer option (NOTE 4x2 or 4x4) All values are shown in pounds unless otherwise stated Payload and Max Trailer Weight values are rounded to the nearest 10 lbs Payload = GVWR - Base Weight GAWRs, GVWRs, and GCWRs should never be exceeded Recommended tongue weight determined by class hitch receiver and hardware limits of upfit Upfit or Aftermarket equipment weight not included in Base Weight
-------	--

**2020 RAM 5500 (DP) BASE WEIGHT GCW AND TRAILER TOW**