

2019 RAM 3500 Trailer Towing Chart - SAE J2807 Compliant.

RAM 3500 4X2 REG CAB TRADESMAN W/8.0' BOX

Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	DRW	3.73	14000	7680	6319	3396	2923	5500	9750	21500	14710
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	DRW	4.10	14000	7680	6319	3396	2923	5500	9750	25000	18210
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	10700	4660	6037	3402	2635	5500	7000	21500	14990
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	10700	4660	6037	3402	2635	5500	7000	24000	17490
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	SRW	3.73	11500	4700	6803	4155	2648	5500	7000	28300	21030
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	DRW	3.73	14000	6910	7094	4148	2946	5500	9750	28300	20740
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	DRW	4.10	14000	6910	7094	4148	2946	5500	9750	30300	22740
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	SRW	3.73	11500	4520	6982	4275	2707	5500	7000	34630	26990
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	DRW	3.73	14000	6570	7430	4324	3106	5500	9750	41600	33700
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	DRW	4.10	14000	6570	7430	4324	3106	5500	9750	43000	35100

RAM 3500 4X2 REG CAB TRADESMAN W/O BOX

Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	10700	5190	5506	3441	2065	5500	7000	21500	14870
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	10700	5190	5506	3441	2065	5500	7000	24000	17370

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb
 Options Weight = 100 lb
 Trailing Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.
 Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for a 5th Wheel or Gooseneck hitch.
 Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailing equipment and tongue weight.
 Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.
8. A fifth-wheel hitch is required for trailers over 23,000 lbs.
9. A Gooseneck hitch is required for trailers over 30,000 lbs.
10. Maximum Capability Configuration.

2019 RAM 3500 Trailer Towing Chart - SAE J2807 Compliant.

RAM 3500 4X2 CREW CAB TRADESMAN W/6.5' BOX

Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	10700	4300	6400	3585	2815	5500	7000	21500	14630
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	10700	4300	6400	3585	2815	5500	7000	24000	17130
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION-6-SPD. AUTOMATIC,68RFE	SRW	3.73	11500	4260	7241	4341	2900	5500	7000	28300	20590
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	SRW	3.73	11500	4120	7383	4450	2932	5500	7000	32240	24320

RAM 3500 4X2 CREW CAB TRADESMAN W/RAMBOX

Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	10700	4160	6545	3583	2962	5500	7000	21500	14490
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	10700	4160	6545	3583	2962	5500	7000	24000	16990
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION-6-SPD. AUTOMATIC,68RFE	SRW	3.73	11500	4110	7386	4363	3023	5500	7000	28300	20440
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	SRW	3.73	11500	3970	7528	4473	3055	5500	7000	32240	23350

RAM 3500 4X2 CREWCAB TRADESMAN W/O BOX

Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	10700	4720	5984	3670	2314	5500	7000	21500	14480
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	10700	4720	5984	3670	2314	5500	7000	24000	16980

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailering Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb
 Options Weight = 100 lb
 Trailering Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.
 Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for a 5th Wheel or Gooseneck hitch.
 Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailering equipment and tongue weight.
 Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.
8. A fifth-wheel hitch is required for trailers over 23,000 lbs.
9. A Gooseneck hitch is required for trailers over 30,000 lbs.
10. Maximum Capability Configuration.

2019 RAM 3500 Trailer Towing Chart - SAE J2807 Compliant.

RAM 3500 4X2 CREW CAB TRADESMAN W/8.0' BOX

Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11100	4530	6567	3727	2840	5500	7000	21500	14460
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11100	4530	6567	3727	2840	5500	7000	24000	16960
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	DRW	3.73	14000	7050	6954	3754	3201	5500	9750	21500	14080
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	DRW	4.10	14000	7050	6954	3754	3201	5500	9750	25000	17580
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	SRW	3.73	12000	4620	7385	4483	2902	5500	7000	28300	20450
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	DRW	3.73	14000	6170	7833	4542	3291	5500	9750	28300	20000
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	DRW	4.10	14000	6170	7833	4542	3291	5500	9750	30300	22000
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	SRW	3.73	12000	4470	7527	4597	2931	5500	7000	33670	25650
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	DRW	3.73	14000	5950	8050	4663	3386	5500	9750	41600	33080
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	DRW	4.10	14000	5950	8050	4663	3386	5500	9750	43000	34480

RAM 3500 4X2 CREWCAB TRADESMAN W/OBOX

Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11100	5080	6019	3749	2270	5500	7000	21500	14370
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11100	5080	6019	3749	2270	5500	7000	24000	16870

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb
 Options Weight = 100 lb
 Trailing Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.
 Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for a 5th Wheel or Gooseneck hitch.
 Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailing equipment and tongue weight.
 Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.
8. A fifth-wheel hitch is required for trailers over 23,000 lbs.
9. A Gooseneck hitch is required for trailers over 30,000 lbs.
10. Maximum Capability Configuration.

2019 RAM 3500 Trailer Towing Chart - SAE J2807 Compliant.												
RAM 3500 4X4 MEGA CAB BIG HORN/LONE STAR 6.5' BOX												
Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	DRW	3.73	14000	6630	7374	4033	3341	5500	9750	21500	13660
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	DRW	4.10	14000	6630	7374	4033	3341	5500	9750	25000	17160
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11400	4420	6978	4011	2967	5500	7000	21500	14050
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11400	4420	6978	4011	2967	5500	7000	24000	16550
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	SRW	3.73	12300	4330	7968	4805	3163	6000	7000	28300	19860
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	DRW	3.73	14000	5670	8332	4851	3481	6000	9750	28300	19500
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	DRW	4.10	14000	5670	8332	4851	3481	6000	9750	30300	21500
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	SRW	3.73	12300	4220	8079	4916	3162	6000	7000	32710	24060
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	DRW	3.73	14000	5420	8577	4990	3588	6000	9750	41600	32550
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	DRW	4.10	14000	5420	8577	4990	3588	6000	9750	43000	33020
RAM 3500 4X4 MEGA CAB BIG HORN/LONE STAR RAMBOX												
Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11400	4280	7123	4009	3114	5500	7000	21500	13910
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11400	4280	7123	4009	3114	5500	7000	24000	16410
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	SRW	3.73	12300	4190	8114	4834	3280	6000	7000	28300	19720
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	SRW	3.73	12300	4080	8224	4945	3279	6000	7000	32710	23280

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailering Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb
 Options Weight = 100 lb
 Trailering Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.
 Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for a 5th Wheel or Gooseneck hitch.
 Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailering equipment and tongue weight.
 Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.
8. A fifth-wheel hitch is required for trailers over 23,000 lbs.
9. A Gooseneck hitch is required for trailers over 30,000 lbs.
10. Maximum Capability Configuration.

2019 RAM 3500 Trailer Towing Chart - SAE J2807 Compliant.

RAM 3500 4X4 REG CAB TRADESMAN 8.0' BOX

Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11000	4600	6403	3698	2704	5500	7000	21500	14630
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11000	4600	6403	3698	2704	5500	7000	24000	17130
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	DRW	3.73	14000	7280	6715	3710	3005	5500	9750	21500	14310
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	DRW	4.10	14000	7280	6715	3710	3005	5500	9750	25000	17810
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	DRW	3.73	14000	6390	7614	4496	3118	6000	9750	28300	20220
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	DRW	4.10	14000	6390	7614	4496	3118	6000	9750	30300	22220
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	SRW	3.73	11800	4610	7195	4442	2753	6000	7000	28300	20640
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	DRW	3.73	14000	6160	7842	4620	3222	6000	9750	41600	33290
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	DRW	4.10	14000	6160	7842	4620	3222	6000	9750	43000	34690
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	SRW	3.73	11800	4460	7341	4551	2790	6000	7000	34540	26440

RAM 3500 4X4 REG CAB TRADESMAN W/O BOX

Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11000	5130	5869	3742	2127	5500	7000	21500	14510
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11000	5130	5869	3742	2127	5500	7000	24000	17010

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb
 Options Weight = 100 lb
 Trailing Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.
 Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for a 5th Wheel or Gooseneck hitch.
 Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailing equipment and tongue weight.
 Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.
8. A fifth-wheel hitch is required for trailers over 23,000 lbs.
9. A Gooseneck hitch is required for trailers over 30,000 lbs.
10. Maximum Capability Configuration.

2019 RAM 3500 Trailer Towing Chart - SAE J2807 Compliant.												
RAM 3500 4X4 CREW CAB TRADESMAN 6.5' BOX												
Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11000	4270	6728	3853	2876	5500	7000	21500	14300
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11000	4270	6728	3853	2876	5500	7000	24000	16800
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC.68RFE	SRW	3.73	11800	4340	7460	4563	2897	6000	7000	28300	20370
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	SRW	3.73	11800	4180	7622	4683	2939	6000	7000	32580	24490
RAM 3500 4X4 CREW CAB TRADESMAN RAMBOX												
Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11000	4140	6863	3872	2991	5500	7000	21500	14170
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11000	4140	6863	3872	2991	5500	7000	24000	16670
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC.68RFE	SRW	3.73	11800	4200	7605	4561	3044	6000	7000	28300	20230
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	SRW	3.73	11800	4030	7767	4681	3086	6000	7000	32580	23750
RAM 3500 4X4 CREWCAB TRADESMAN W/O BOX												
Engine	Trans.	SRW/DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11000	4720	6278	3927	2351	5500	7000	21500	14180
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11000	4720	6278	3927	2351	5500	7000	24000	16680

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb
 Options Weight = 100 lb
 Trailing Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.
 Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for a 5th Wheel or Gooseneck hitch.
 Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailing equipment and tongue weight.
 Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.
8. A fifth-wheel hitch is required for trailers over 23,000 lbs.
9. A Gooseneck hitch is required for trailers over 30,000 lbs.
10. Maximum Capability Configuration.

2019 RAM 3500 Trailer Towing Chart - SAE J2807 Compliant.

RAM 3500 4X4 CREW CAB TRADESMAN 8.0' BOX

Engine	Trans.	SRW/ DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	DRW	3.73	14000	6680	7317	4058	3259	5500	9750	21500	13710
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	DRW	4.10	14000	6680	7317	4058	3259	5500	9750	25000	17210
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11400	4480	6920	4017	2903	5500	7000	21500	14110
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11400	4480	6920	4017	2903	5500	7000	24000	16610
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	SRW	3.73	12300	4580	7723	4751	2973	6000	7000	28300	20110
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	DRW	3.73	14000	5840	8159	4818	3341	6000	9750	28300	19670
6.7L I6 CUMMINS TURBO DIESEL ENGINE	TRANSMISSION -6-SPD. AUTOMATIC,68RFE	DRW	4.10	14000	5840	8159	4818	3341	6000	9750	30300	21670
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	SRW	3.73	12300	4420	7878	4872	3005	6000	7000	33610	25150
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	DRW	3.73	14000	5600	8396	4955	3441	6000	9750	41600	32730
6.7L I6 CUMMINS HO TURBO DIESEL ENG	6 SPD AUTO AISIN NEW HD TRANSMISSION	DRW	4.10	14000	5600	8396	4955	3441	6000	9750	43000	34130

RAM 3500 4X4 CREWCAB TRADESMAN W/O BOX

Engine	Trans.	SRW/ DRW	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
						Total	Front	Rear	Front	Rear		
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	3.73	11400	5020	6377	4050	2326	5500	7000	21500	14010
6.4L V8 MID DUTY HEMI MDS ENGINE	8-SPD AUTO 8HP75-LCV TRANSMISSION	SRW	4.10	11400	5020	6377	4050	2326	5500	7000	24000	16510

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb
 Options Weight = 100 lb
 Trailing Equipment Weight: 75 lb for Conventional Hitch, 70 lb for Gooseneck and 250 lb for 5th Wheel.
 Tongue weight: 10 percent of the gross trailer weight for Conventional Hitch, 15 percent of the gross trailer weight for a 5th Wheel or Gooseneck hitch.
 Payload and GAWR should never be exceeded and must account for all of the above weights, including the appropriate trailing equipment and tongue weight.
 Box Off Body Completion Weight = 80 lb per foot from end of cab to end of frame.
8. A fifth-wheel hitch is required for trailers over 23,000 lbs.
9. A Gooseneck hitch is required for trailers over 30,000 lbs.
10. Maximum Capability Configuration.